

## 1206SFF150F/63-2

## 1206SFF150F/63-2 Information



Part Number	1206SFF150F/63-2
Manufacturer	Littelfuse Inc.
Category	Circuit Protection Fuses
Description	FUSE BOARD MOUNT 1.5A 63VDC 1206
Package	1206 (3216 Metric)
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

#### For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 1206SFF150F/63-2 Specifications

Manufacturer   Littelfuse Inc.     Category   Circuit Protection     Fuses   Fuses     Package   1206 (3216 Metric)     Series   SFF     Fuse Type   Board Mount (Cartridge Style Excluded)     Current Rating   1.5A     Voltage Rating - AC   -     Voltage Rating - DC   63V     Response Time   Fast     Package / Case   1206 (3216 Metric)     Munufing Type   Surface Mount     Manufacturer   60A     Package / Case   1206 (3216 Metric)     Mounting Type   Surface Mount     Metring 12t   0.025     Approvals   UL     Operating Temperature   -5°C ~ 125°C     Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)			
CategoryCircuit ProtectionFusesPackage1206 (3216 Metric)SeriesSFFFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating1.5AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.00mm)	Manufacturer Part Number	1206SFF150F/63-2	
Fuses     Package   1206 (3216 Metric)     Series   SFF     Fuse Type   Board Mount (Cartridge Style Excluded)     Current Rating   1.5A     Voltage Rating - AC   -     Voltage Rating - DC   63V     Response Time   Fast     Package / Case   1206 (3216 Metric)     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A     Melting 12t   0.025     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Manufacturer	Littelfuse Inc.	
Package1206 (3216 Metric)SeriesSFFFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating1.5AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.025ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Category	Circuit Protection	
Series   SFF     Fuse Type   Board Mount (Cartridge Style Excluded)     Current Rating   1.5A     Voltage Rating - AC   -     Voltage Rating - DC   63V     Response Time   Fast     Package / Case   1206 (3216 Metric)     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A     Melting I2t   0.025     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating1.5AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.025ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Package	1206 (3216 Metric)	
Current Rating1.5AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.025ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Series	SFF	
Voltage Rating - AC   -     Voltage Rating - DC   63V     Response Time   Fast     Package / Case   1206 (3216 Metric)     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A     Melting I2t   0.025     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.025ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Current Rating	1.5A	
Response Time   Fast     Package / Case   1206 (3216 Metric)     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A     Melting I2t   0.025     Approvals   UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Voltage Rating - AC	-	
Package / Case 1206 (3216 Metric)   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Melting I2t 0.025   Approvals UL   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Voltage Rating - DC	63V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.025ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Response Time	Fast	
Breaking Capacity @ Rated Voltage   50A     Melting I2t   0.025     Approvals   UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Package / Case	1206 (3216 Metric)	
Melting I2t   0.025     Approvals   UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Mounting Type	Surface Mount	
Approvals   UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Breaking Capacity @ Rated Voltage	50A	
Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Melting I2t	0.025	
Color   -     Size / Dimension   0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Approvals	UL	
Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors?	Size / Dimension	0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	
			Report errors?

### 1206SFF150F/63-2 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## 1206SFF150F/63-2 Payment Methods





If you have any question about 1206SFF150F/63-2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com