

1206SFF200F/63-2

1206SFF200F/63-2 Information



Part Number	1206SFF200F/63-2		
Manufacturer	Littelfuse Inc.		
Category	Circuit Protection Fuses		
Description	FUSE BOARD MOUNT 2A 63VDC 1206		
Package	1206 (3216 Metric)		
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com		



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1206SFF200F/63-2 Specifications

Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.07ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)			
Category Circuit Protection Fuses Package 1206 (3216 Metric) Series SFF Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2A Voltage Rating - AC - Voltage Rating - DC 63V Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Parkang Capacity @ Rated Voltage 50A Approvals UL Operating Temperature -55°C ~ 125°C Color - Ster / Dimension 1.26"L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Manufacturer Part Number	1206SFF200F/63-2	
Fuses Package 1206 (3216 Metric) Series SFF Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2A Voltage Rating - AC - Voltage Rating - DC 63V Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Approvals UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126"L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Manufacturer	Littelfuse Inc.	
Package1206 (3216 Metric)SeriesSFFFuse TypeBoard Mount (Cartridge Style Excluded)Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.07ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Category	Circuit Protection	
SeriesSFFFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)		Fuses	
Fuse Type Board Mount (Cartridge Style Excluded) Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2A Voltage Rating - AC - Voltage Rating - DC 63V Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.07 Approvals UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126"L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Package	1206 (3216 Metric)	
Current Rating2AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.07ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Series	SFF	
Voltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.07ApprovalsULOperating Temperature-5°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.07ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Current Rating	2A	
Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.07 Approvals UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Voltage Rating - AC	-	
Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.07 Approvals UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Voltage Rating - DC	63V	
Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.07 Approvals UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Response Time	Fast	
Breaking Capacity @ Rated Voltage 50A Melting I2t 0.07 Approvals UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Package / Case	1206 (3216 Metric)	
Melting 12t 0.07 Approvals UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Mounting Type	Surface Mount	
Approvals UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Breaking Capacity @ Rated Voltage	50A	
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Melting I2t	0.07	
Color - Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Approvals	UL	
Size / Dimension 0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors?	Size / Dimension	0.126" L x 0.063" W x 0.043" H (3.20mm x 1.60mm x 1.10mm)	
1			Report errors?

1206SFF200F/63-2 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1206SFF200F/63-2 Payment Methods





If you have any question about 1206SFF200F/63-2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com