

1206SFP800F/24-2

1206SFP800F/24-2 Information



Part Number	1206SFP800F/24-2	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Fuses	
Description	FUSE BOARD MOUNT 8A 24VDC 1206	
Package	1206 (3216 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1206SFP800F/24-2 Specifications

Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Fuses Package 1206 (3216 Metric) Series - Fuse Type Board Mount (Catrridge Style Excluded) Current Rating 8A Voltage Rating - AC - Voltage Rating - DC 24V Response Time - Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 60 Approvals - Approvals - Operating Temperature -S5°C ~ 125°C Color -			
Category Circuit Protection Fuses Fuses Package 1206 (3216 Metric) Series - Fuse Type Board Mount (Catridge Style Excluded) Current Rating 8A Voltage Rating - AC - Voltage Rating - DC 24V Response Time - Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 80A Melting 12t 60 Approvals - Operating Temperature - Color - Size / Dimension -	Manufacturer Part Number	1206SFP800F/24-2	
FusesPackage1206 (3216 Metric)Series-Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating8AVoltage Rating - AC-Voltage Rating - DC24VResponse Time-Package / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage80AMelting 12t60Approvals-Operating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Manufacturer	Littelfuse Inc.	
Package1206 (3216 Metric)Series-Fuse TypeBoard Mount (Cartridge Style Excluded)Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating8AVoltage Rating - AC-Voltage Rating - DC24VResponse Time-Package / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage80AMelting I2t60Approvals-Operating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Category	Circuit Protection	
Series - Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 8A Voltage Rating - AC - Voltage Rating - DC 24V Response Time - Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 80A Melting I2t 60 Approvals - Operating Temperature - Color - Stize / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating8AVoltage Rating - AC-Voltage Rating - DC24VResponse Time-Package / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage80AMelting I2t60Approvals-Operating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Package	1206 (3216 Metric)	
Current Rating 8A Voltage Rating - AC - Voltage Rating - DC 24V Response Time - Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 80A Melting I2t 60 Approvals - Operating Temperature -55°C ~ 125°C Color - Stize / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Series	-	
Voltage Rating - AC - Voltage Rating - DC 24V Response Time - Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 80A Melting I2t 60 Approvals - Operating Temperature - Color - Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC24VResponse Time-Package / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage80AMelting I2t60Approvals-Operating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Current Rating	8A	
Response Time - Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 80A Melting I2t 60 Approvals - Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Voltage Rating - AC	-	
Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 80A Melting I2t 60 Approvals - Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Voltage Rating - DC	24V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage80AMelting I2t60Approvals-Operating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Response Time	-	
Breaking Capacity @ Rated Voltage 80A Melting I2t 60 Approvals - Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Package / Case	1206 (3216 Metric)	
Melting I2t 60 Approvals - Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Mounting Type	Surface Mount	
Approvals - Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Breaking Capacity @ Rated Voltage	80A	
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Melting I2t	60	
Color - Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Approvals	-	
Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors?	Size / Dimension	0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	
			Report errors?

1206SFP800F/24-2 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1206SFP800F/24-2 Payment Methods





If you have any question about 1206SFP800F/24-2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com