

# 1206SFS100F/63-2

### 1206SFS100F/63-2 Information



Part Number	1206SFS100F/63-2	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Fuses	
Description	FUSE BOARD MOUNT 1A 63VDC 1206	
Package	1206 (3216 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

#### For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# 1206SFS100F/63-2 Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFusesPackage1206 (3216 Metric)SeriesSFSFuse TypeBoard Mount (Cartridge Style Excluded)Current RatingIAVoltage Rating - AC-Voltage Rating - DC63VResponse TimeSlowPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMetling 12t0.11ApprovalsULOperating Temperature-55°C ~ 125°CColor-			
CategoryCircuit ProtectionFusesPackage1206 (3216 Metric)SeriesSFSFuse TypeBoard Mount (Catridge Style Excluded)Current Rating1AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeSlowPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AApprovalsULOperating Temperature.55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Manufacturer Part Number	1206SFS100F/63-2	
FusesPackage1206 (3216 Metric)SeriesSFSFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating1AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeSlowPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting 12t0.11ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Manufacturer	Littelfuse Inc.	
Package1206 (3216 Metric)SeriesSFSFuse TypeBoard Mount (Cartridge Style Excluded)Current RatingIAVoltage Rating - AC-Voltage Rating - DC63VResponse TimeSlowPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMetting I2t0.11ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Category	Circuit Protection	
Series SFS   Fuse Type Board Mount (Cartridge Style Excluded)   Current Rating 1A   Voltage Rating - AC -   Voltage Rating - DC 63V   Response Time Slow   Package / Case 1206 (3216 Metric)   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Melting I2t 0.11   Approvals UL   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating1AVoltage Rating - AC-Voltage Rating - DC63VResponse TimeSlowPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMetting I2t0.11ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 0.97mm)	Package	1206 (3216 Metric)	
Current Rating 1A   Voltage Rating - AC -   Voltage Rating - DC 63V   Response Time Slow   Package / Case 1206 (3216 Metric)   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Melting 12t 0.11   Approvals UL   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Series	SFS	
Voltage Rating - AC-Voltage Rating - DC63VResponse TimeSlowPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.11ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC63VResponse TimeSlowPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.11ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Current Rating	1A	
Response Time Slow   Package / Case 1206 (3216 Metric)   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Melting I2t 0.11   Approvals UL   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Voltage Rating - AC	-	
Package / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.11ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Voltage Rating - DC	63V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.11ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Response Time	Slow	
Breaking Capacity @ Rated Voltage50AMelting I2t0.11ApprovalsULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Package / Case	1206 (3216 Metric)	
Melting I2t 0.11   Approvals UL   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Mounting Type	Surface Mount	
Approvals UL   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Breaking Capacity @ Rated Voltage	50A	
Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Melting I2t	0.11	
Color -   Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Approvals	UL	
Size / Dimension 0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors?	Size / Dimension	0.126" L x 0.063" W x 0.038" H (3.20mm x 1.60mm x 0.97mm)	
			Report errors?

### 1206SFS100F/63-2 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### 1206SFS100F/63-2 Payment Methods





If you have any question about 1206SFS100F/63-2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com