



1206Y0161P80BFT Information

Heisener.com

Part Number 1206Y0161P80BFT
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 1.8PF 16V C0G/NP0 1206

Package 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1206Y0161P80BFT Specifications

Manufacturer Part Number 1206Y0161P80BFT Manufacturer Knowles Syfer Category Capacitors Package 1206 (3216 Metric) Series FlexiCap? Capacitance 1.8pF Tolerance ±0.1pF Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package 1206 (3216 Metric) Series FlexiCap? Capacitance 1.8pF Tolerance ±0.1pF Voltage - Rated 16V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1206Y0161P80BFT
Package 1206 (3216 Metric) Series FlexiCap? Capacitance 1.8pF Tolerance ±0.1pF Voltage - Rated 16V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1206 (3216 Metric) Series FlexiCap? Capacitance 1.8pF Tolerance ±0.1pF Voltage - Rated 16V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 1.8pF Tolerance ±0.1pF Voltage - Rated 16V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 1.8pF Tolerance ±0.1pF Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Package	1206 (3216 Metric)
Tolerance ±0.1pF Voltage - Rated 16V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Series	FlexiCap?
Voltage - Rated Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style	Capacitance	1.8pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) Thickness (Max) 0.063" (1.60mm) Lead Spacing Lead Style -	Tolerance	±0.1pF
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Features	High Temperature
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Applications	High Reliability
Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1206 (3216 Metric)
Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.063" (1.60mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1206Y0161P80BFT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1206Y0161P80BFT Payment Methods

































If you have any question about 1206Y0161P80BFT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com