



1206Y0250681KCR Information

Heisener.com

Part Number 1206Y0250681KCR
Manufacturer Knowles Syfer

Category Capacitors
Ceramic Capacitors

Description CAP CER 1206 **Package** 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1206Y0250681KCR Specifications

Manufacturer Part Number 1206Y0250681KCR Manufacturer Knowles Syfer Category Capacitors Package 1206 (3216 Metric) Series FlexiCap? Capacitance 680pF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package 1206 (3216 Metric) Series FlexiCap? Capacitance 680pF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1206Y0250681KCR
Package 1206 (3216 Metric) Series FlexiCap? Capacitance 680pF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1206 (3216 Metric) Series FlexiCap? Capacitance 680pF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 680pF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 680pF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Package	1206 (3216 Metric)
Tolerance ±10% Voltage - Rated 25V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Series	FlexiCap?
Voltage - Rated25VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Capacitance	680pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) Thickness (Max) Lead Spacing - Lead Style - COG, NP0 (1B) COG, NP0 (1B) Soft Termination 125°C 125°C Soft Termination 100 100 100 100 100 100 100 1	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Voltage - Rated	25V
Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0 (1B)
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1206 (3216 Metric)
Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.063" (1.60mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1206Y0250681KCR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1206Y0250681KCR Payment Methods



















1206Y0250681KCR Shipping Methods













If you have any question about 1206Y0250681KCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com