


1206Y0500122FCR

Request a Quote

1206Y0500122FCR Information

	Heisener.com	Part Number	1206Y0500122FCR
		Manufacturer	Knowles Syfer
		Category	Capacitors Ceramic Capacitors
		Description	CAP CER 1206
		Package	1206 (3216 Metric)
			For the pricing/inventory/lead time, please contact
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1206Y0500122FCR Specifications

Manufacturer Part Number 1206Y0500122FCR Manufacturer Knowles Syfer Category Capacitors Package 1206 (3216 Metric) Package 1206 (3216 Metric) Series FlexiCap? Capacitance 1200pF Tolerance ±1% Voltage - Rated 50V Operating Temperature 050° C ~ 125°C Pactures Soft Termination Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package (Max) - Strice Mounts (Max) - Thickness (Max) - Strice Mounts (Max) -			
CategoryCapacitorsPackage1206 (3216 Metric)Package1206 (3216 Metric)SeriesFlexiCap?Capacitance1200pFTolerance±1%Voltage - Rated50VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Manufacturer Part Number	1206Y0500122FCR	
Indext of the section of the sectio	Manufacturer	Knowles Syfer	
Package1206 (3216 Metric)SeriesFlexiCap?Capacitance1200pFTolerance±1%Voltage - Rated50VTemperature CoefficientC0G, NP0 (1B)Operating Temperature55°C ~ 125°CFeaturesSoft TerminationApplications-Applications-Mounting TypeSurface Mount, MLCCPackage / Case0.126° L x 0.063° W (3.20mm x 1.60mm)Fickers (Max)0.063° (1.60mm)Height - Seated (Max)-Applex (Max)0.063° (1.60mm)Lead Spacing-Lead Style-	Category	Capacitors	
SeriesFlexiCap?Capacitance1200pFTolerance±1%Voltage - Rated50VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.63° (1.60mm)Lead Spacing-Lead Style-		Ceramic Capacitors	
Capacitance1200pFTolerance±1%Voltage - Rated50VTemperature CoefficientCOG, NP0 (1B)Operating Temperature55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Style-Starten <td>Package</td> <td>1206 (3216 Metric)</td>	Package	1206 (3216 Metric)	
Tolerance±1%Voltage - Rated50VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55° ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFaiture Rate-Mounting TypeSuf Cae Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Hight - Seated (Max)-Highten Seated (Max)-Lead Spaine-Lead Style-Statel Style-Statel Style-Statel Style-Statel Style- <td>Series</td> <td>FlexiCap?</td>	Series	FlexiCap?	
Voltage - Rated50VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-State Style-State Style-State Style-State Style-State Style-State Style- </td <td>Capacitance</td> <td>1200pF</td>	Capacitance	1200pF	
Temperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-State Style-	Tolerance	±1%	
Operating Temperature.55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Voltage - Rated	50V	
FeaturesSoft TerminationFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0 (1B)	
Ratings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C	
ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Features	Soft Termination	
FriFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Ratings	-	
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Applications	Boardflex Sensitive	
Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Failure Rate	-	
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC	
Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Package / Case	1206 (3216 Metric)	
Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)	
Lead Spacing-Lead Style-	Height - Seated (Max)	-	
Lead Style -	Thickness (Max)	0.063" (1.60mm)	
· ·	Lead Spacing	-	
Report errors?	Lead Style	-	
		Report errors?	

1206Y0500122FCR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1206Y0500122FCR Payment Methods



If you have any question about 1206Y0500122FCR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com