

1206Y2001P50CFT

1206Y2001P50CFT Information

Heisener.com	Part Number Manufacturer Category Description Package	1206Y2001P50CFT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 1.5PF 200V C0G/NP0 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1206Y2001P50CFT Specifications

Manufacturer Part Number 1206Y2001P50CPT Manufacturer Knowles Syfer Category Capacitors Package 1206 (3216 Metric) Package 1206 (3216 Metric) Series FexiCap? Capacitance 1.5pF Tolerance 40.25pF Voltage - Rated 200V Operating Temperature 05°C ~ 125°C Pactage High Temperature Applications High Reliability Fatures High Reliability Applications Surface Mount, MLCC Mounting Type Surface Mount, Surface Mount, and		
CategoryCapacitorsPackage1206 (3216 Metric)Package1206 (3216 Metric)SeriesFlexiCap?Capacitance1.5pFTolerance±0.25pFVoltage - Rated200VCoperating TemperatureC0G, NP0Operating Temperature.55°C ~ 125°CFeaturesHigh TemperatureApplications.Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063" W (3.20mm x 1.60mm)Hight - Seated (Max).Thickness (Max)0.663" (1.60mm)Lead Spacing.Lead Style.	Manufacturer Part Number	1206Y2001P50CFT
Ceranic CapacitorsPackage1206 (3216 Metric)SeriesFlexiCap?Capacitance1.5pFTolerance±0.25pFVoltage - Rated00VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Applications-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.63" (1.60mm)Height - Seated (Max)-Height Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Manufacturer	Knowles Syfer
Package1206 (3216 Metric)SeriesFlexiCap?Capacitance1.5pFTolerance40.25pFVoltage - Rated00VComperature CoefficientC0G, NP0Operating Temperature55°C ~ 125°CFeaturesHigh TemperatureApplications-Applications TypeSurface Mount, MLCCNourting Type106 (3216 Metric)Size / Dimension.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max).063° (1.60mm)Head Spacing.Lead Style.	Category	Capacitors
SeriesFlexiCap?Capacitance1.5pFTolerance±0.25pFVoltage - Rated200VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Hight - Seated (Max)-Thickness (Max)0.063° (1.60mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance1.5pFTolerance#0.25pFVoltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.126°L x 0.063° W (3.20mm x 1.60mm)Hight - Seated (Max)-Thickness (Max)0.063°' (1.60mm)Lead Spacing-Lead Style-	Package	1206 (3216 Metric)
Tolerance±0.25pFVoltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing0.063" (1.60mm)Lead Spacing-Lead Style-	Series	FlexiCap?
Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-5°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.126° L x 0.063° W (3.20mm x 1.60mm)Size / Dimension-Height - Seated (Max)-Lead Spacing0.063° (1.60mm)Lead Style-State Style-	Capacitance	1.5pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Hight - Seated (Max)-Thickness (Max)0.063° (1.60mm)Lead Spacing-Lead Style-	Tolerance	±0.25pF
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Voltage - Rated	200V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Features	High Temperature
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Applications	High Reliability
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Package / Case	1206 (3216 Metric)
Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.063" (1.60mm)
-	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1206Y2001P50CFT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1206Y2001P50CFT Payment Methods





If you have any question about 1206Y2001P50CFT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com