

## 121-13-640-41-001000

#### 121-13-640-41-001000 Information

Heisener.com	 121-13-640-41-001000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 40POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 121-13-640-41-001000 Specifications

Manufacturer Part Number121-13-640-41-001000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsSockets for ICs, TransistorsSockets for ICs, TransistorsPackage-Series121TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)FreminationWire WrapFeaturesOpen FrameContact Finish - PostGoldContact Finish Post0.100" (2.54mm)Fortact Finish - Post0.100" (2.54mm)FeaturesSocket Socket Socke			
CategoryConnectionCategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series121TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm) Row SpacingContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Fickness - Post0.100" (2.54mm)	Manufacturer Part Number	121-13-640-41-001000	
Sockets for ICs, TransistorsPackage-Series121TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - Post10µin (0.25µm)	Manufacturer	Mill-Max Manufacturing Corp.	
Package.Series121TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBerylium CopperContact Material - MatingDen FrameFeaturesOpen FrameFreminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post0.100" (2.54mm)Fortart Finish - PostGoldContact Finish - PostGoldContact Finish - PostGold	Category	Connectors, Interconnects	
Series121TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostJoung (2.54mm)Contact Finish - PostGold		Sockets for ICs, Transistors	
TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - Post10µin (0.25µm)	Package	-	
Number of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish - PostGoldContact Finish - PostI0µin (0.25µm)	Series	121	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Туре	DIP, 0.6" (15.24mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post10µin (0.25µm)	Number of Positions or Pins (Grid)	40 (2 x 20)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Contact Material - Mating	Beryllium Copper	
TerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Features	Open Frame	
Contact Finish - PostGoldContact Finish Thickness - Post10μin (0.25μm)	Termination	Wire Wrap	
Contact Finish Thickness - Post 10µin (0.25µm)	Pitch - Post	0.100" (2.54mm)	
	Contact Finish - Post	Gold	
Contact Material - Post Brass Alloy	Contact Finish Thickness - Post	10µin (0.25µm)	
Contact Matchai Tost Diass Miloy	Contact Material - Post	Brass Alloy	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C	
Report errors			Report errors?

#### 121-13-640-41-001000 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## 121-13-640-41-001000 Payment Methods





If you have any question about 121-13-640-41-001000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com