



## 12102U151GAT2A Information



For Reference Only

Part Number 12102U151GAT2A
Manufacturer AVX Corporation
Category Capacitors

Capacitors
Ceramic Capacitors

**Description** CAP CER 150PF 200V C0G/NP0 1210

**Package** 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 12102U151GAT2A Specifications

Manufacturer Part Number         12102U15IGAT2A           Manufacturer         AVX Corporation           Category         Capacitors           Package         1210 (3225 Metric)           Series         U           Capacitance         150pF           Tolerance         ±2%           Voltage - Rated         200V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Ultra-Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.49mm)           Height - Seated (Max)         -           Thickness (Max)         0.055" (1.40mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         1210 (3225 Metric)           Series         U           Capacitance         150pF           Tolerance         ±2%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Ultra-Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.49mm)           Height - Seated (Max)         -           Thickness (Max)         0.055" (1.40mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	12102U151GAT2A
Package         1210 (3225 Metric)           Series         U           Capacitance         150pF           Tolerance         ±2%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Ultra-Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.49mm)           Height - Seated (Max)         -           Thickness (Max)         0.055" (1.40mm)           Lead Spacing         -           Lead Style         -	Manufacturer	AVX Corporation
Package         1210 (3225 Metric)           Series         U           Capacitance         150pF           Tolerance         ±2%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Ultra-Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.49mm)           Height - Seated (Max)         -           Thickness (Max)         0.055" (1.40mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         U           Capacitance         150pF           Tolerance         ±2%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Ultra-Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.49mm)           Height - Seated (Max)         -           Thickness (Max)         0.055" (1.40mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         150pF           Tolerance         ±2%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Ultra-Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.49mm)           Height - Seated (Max)         -           Thickness (Max)         0.055" (1.40mm)           Lead Spacing         -           Lead Style         -	Package	1210 (3225 Metric)
Tolerance ±2%  Voltage - Rated 200V  Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C  Features Ultra-Low ESR  Ratings -  Applications RF, Microwave, High Frequency  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 1210 (3225 Metric)  Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.49mm)  Height - Seated (Max) -  Thickness (Max) 0.055" (1.40mm)  Lead Spacing -  Lead Style -	Series	U
Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesUltra-Low ESRRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.49mm)Height - Seated (Max)-Thickness (Max)0.055" (1.40mm)Lead Spacing-Lead Style-	Capacitance	150pF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  Ultra-Low ESR  Ratings  - Applications  RF, Microwave, High Frequency  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  1210 (3225 Metric)  Size / Dimension  0.126" L x 0.098" W (3.20mm x 2.49mm)  Height - Seated (Max)  Thickness (Max)  0.055" (1.40mm)  Lead Spacing  - Lead Style	Tolerance	±2%
Operating Temperature-55°C ~ 125°CFeaturesUltra-Low ESRRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.49mm)Height - Seated (Max)-Thickness (Max)0.055" (1.40mm)Lead Spacing-Lead Style-	Voltage - Rated	200V
Features  Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.49mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - RF, Microwave, High Frequency Failure Rate - Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.49mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.49mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing - Lead Style -	Features	Ultra-Low ESR
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.49mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.49mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing - Lead Style -	Applications	RF, Microwave, High Frequency
Package / Case       1210 (3225 Metric)         Size / Dimension       0.126" L x 0.098" W (3.20mm x 2.49mm)         Height - Seated (Max)       -         Thickness (Max)       0.055" (1.40mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.126" L x 0.098" W (3.20mm x 2.49mm)         Height - Seated (Max)       -         Thickness (Max)       0.055" (1.40mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.055" (1.40mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.49mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.055" (1.40mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

### 12102U151GAT2A Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 12102U151GAT2A Payment Methods



















## 12102U151GAT2A Shipping Methods













If you have any question about 12102U151GAT2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com