



12105C335KAZ2A Information



For Reference Only

Part Number 12105C335KAZ2A Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 3.3UF 50V X7R 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









12105C335KAZ2A Specifications

Manufacturer Part Number 12105C335KAZ2A Manufacturer AVX Corporation Category Capacitors Package 1210 (3225 Metric) Series FLEXITERM? Capacitance 3.3μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)		
Category Capacitors Package 1210 (3225 Metric) Series FLEXITERM? Capacitance 3.3μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Manufacturer Part Number	12105C335KAZ2A
Ceramic CapacitorsPackage1210 (3225 Metric)SeriesFLEXITERM?Capacitance3.3μFTolerance±10%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)	Manufacturer	AVX Corporation
Package1210 (3225 Metric)SeriesFLEXITERM?Capacitance3.3μFTolerance±10%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)	Category	Capacitors
SeriesFLEXITERM?Capacitance3.3μFTolerance±10%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)		Ceramic Capacitors
Capacitance $3.3 \mu F$ Tolerance $\pm 10\%$ Voltage - Rated $50V$ Temperature CoefficientX7ROperating Temperature -55° C ~ 125° CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case $1210 (3225 Metric)$	Package	1210 (3225 Metric)
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Series	FLEXITERM?
Voltage - Rated Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Capacitance	3.3µF
Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Tolerance	$\pm 10\%$
Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Voltage - Rated	50V
Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Temperature Coefficient	X7R
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric)	Applications	Boardflex Sensitive
Package / Case 1210 (3225 Metric)	Failure Rate	-
	Mounting Type	Surface Mount, MLCC
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)	Package / Case	1210 (3225 Metric)
	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Height - Seated (Max)	Height - Seated (Max)	-
Thickness (Max) 0.110" (2.79mm)	Thickness (Max)	0.110" (2.79mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

12105C335KAZ2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

12105C335KAZ2A Payment Methods



















12105C335KAZ2A Shipping Methods













If you have any question about 12105C335KAZ2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com