



1210CC223KAZ1A Information



For Reference Only

Part Number 1210CC223KAZ1A Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.022UF 630V X7R 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1210CC223KAZ1A Specifications

Manufacturer Part Number 1210CC223KAZ1A Manufacturer AVX Corporation Category Capacitors Package 1210 (3225 Metric) Series FLEXITERM? Capacitance 0.022μF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.071" (1.80mm)		
Category Capacitors Package 1210 (3225 Metric) Series FLEXITERM? Capacitance 0.022μF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Manufacturer Part Number	1210CC223KAZ1A
Package 1210 (3225 Metric) Series FLEXITERM? Capacitance 0.022μF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Manufacturer	AVX Corporation
Package 1210 (3225 Metric) Series FLEXITERM? Capacitance 0.022µF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient X7R Operating Temperature 55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max)	Category	Capacitors
Series FLEXITERM? Capacitance 0.022μF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -		Ceramic Capacitors
Capacitance0.022μFTolerance±10%Voltage - Rated630VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-	Package	1210 (3225 Metric)
Tolerance ±10% Voltage - Rated 630V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max)	Series	FLEXITERM?
Voltage - Rated Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension Height - Seated (Max) - 630V X7R A7R Boardflex Sensitive - Surface Mount, High Voltage Surface Mount, MLCC - Surface Mount, MLCC - Surface Mount, MLCC - O.126" L x 0.098" W (3.20mm x 2.50mm)	Capacitance	0.022μF
Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension Height - Seated (Max) - X7R X7R -55°C ~ 125°C Soft Termination, High Voltage 1210 (3225 Metric) Surface Mount, MLCC	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Voltage - Rated	630V
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Temperature Coefficient	X7R
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Applications	Boardflex Sensitive
Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Failure Rate	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)	Package / Case	1210 (3225 Metric)
	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Thickness (Max) 0.071" (1.80mm)	Height - Seated (Max)	-
	Thickness (Max)	0.071" (1.80mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

1210CC223KAZ1A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1210CC223KAZ1A Payment Methods





















1210CC223KAZ1A Shipping Methods













If you have any question about 1210CC223KAZ1A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com