

1210J0100273MXT

1210J0100273MXT Information

Heisener.com Ottarierice card terr	 1210J0100273MXT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 0.027UF 10V X7R 1210 1210 (3225 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1210J0100273MXT Specifications

Manufacturer Part Number1210J0100273MXTManufacturerKnowles SyferCapacitorsCapacitorsCeramic Capacitors1210 (3225 Metric)ackage.210 (3225 Metric)eries.Capacitance0.027µFolerance±20%voltage - Rated10Vcemperature CoefficientX7R (2R1)operating Temperature.55°C ~ 125°CeaturesEpoxy Mountableatings.atings.atings.atings.Atiomotive.Atomotive.Atomotive.Atomotive.Atomotive.Atomoting TypeSurface Mount, MLCC
CapacitorsCeramic Capacitorsackage1210 (3225 Metric)eries-capacitance0.027µFolerance±20%voltage - Rated10Voperating Temperature>55°C ~ 125°CeaturesEpoxy Mountableatings-ApplicationsAutomotiveatinge Rated-atinge Rated-atinge Rated-atinge Rated-atinge Rated-atinge Rated-atinge Rated-atinge Rated-atinge Rated-atinge Rate-atinge Rate-
Ceramic Capacitorsackage1210 (3225 Metric)eries-Capacitance0.027μFcolerance±20%Voltage - Rated10Vcomperature CoefficientX7R (2R1)comperating Temperature-55°C ~ 125°CceturesEpoxy Mountablecatings-AutomotiveAutomotivecating Rate-
ackage1210 (3225 Metric)eries-Capacitance0.027μFcolerance±20%Voltage - Rated10Vcomperature CoefficientX7R (2R1)operating Temperature-55°C ~ 125°CeaturesEpoxy Mountablecatings-seplicationsAutomotiveadure Rate-adure Rate-
eries-Capacitance0.027μFSolerance±20%Voltage - Rated10VVemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CeaturesEpoxy Mountablestatings-AutomotiveAutomotiveauture Rate-
Papacitance0.027μFPolerance±20%Poltage - Rated10VPerperature CoefficientX7R (2R1)Poperating Temperature-55°C ~ 125°CPeraturesEpoxy MountablePatings-AutomotiveAutomotivePalure Rate-
Polerance±20%Polage - Rated10VPemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CPetaturesEpoxy MountablePatings-ApplicationsAutomotivePatine Rate-
Yoltage - Rated10VYemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CYeaturesEpoxy MountableYeatings-ApplicationsAutomotiveYeature Rate-
Permerature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CeaturesEpoxy Mountableatings-ApplicationsAutomotiveailure Rate-
Operating Temperature-55°C ~ 125°CeaturesEpoxy Mountableatings-applicationsAutomotiveailure Rate-
PeaturesEpoxy MountableLatings-ApplicationsAutomotiveValue Rate-
Latings-ApplicationsAutomotiveailure Rate-
Automotive
ailure Rate -
Iounting Type Surface Mount, MLCC
ackage / Case 1210 (3225 Metric)
ize / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)
leight - Seated (Max) -
Thickness (Max) 0.079" (2.00mm)
ead Spacing -
ead Style -
Report errors?

1210J0100273MXT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1210J0100273MXT Payment Methods





If you have any question about 1210J0100273MXT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com