

# 1210J5000122MDT

equest a Quote

#### 1210J5000122MDT Information

	Part Number	1210J5000122MDT	
	Manufacturer	Knowles Syfer	
Heisener.com	Category	Capacitors Ceramic Capacitors	
	Description	CAP CER 1200PF 500V X7R 1210	
	Package	1210 (3225 Metric)	i
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	1



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 1210J5000122MDT Specifications

Manufacturer Part Number   1210/5000122MDT     Manufacturer   Knowles Syfer     Capacitors   Capacitors     Caramic Capacitors   1210 (3225 Metric)     eries   -     Capacitance   1200pF     voltage - Rated   500V     Voltage - Rated   500V     Vertures   410 (325°C     vertures   High Temperature     values   -     Autors   High Reliability     ailure Rate   -     Younting Type   Surface Mount, MLCC     Younting Type   1210 (3225 Metric)
CapacitorsCapacitorsCacamic Capacitorstackage1210 (3225 Metric)eries-Capacitance1200pF'olerance±20%'olerance500V'emperature CoefficientX7ROperating Temperature-55°C ~ 125°C'eaturesHigh Temperature'adiures Ated-Atafings-'adiure Rate-Youting TypeSurface Mount, MLCC
Ceramic Capacitorsackage1210 (3225 Metric)eries-Capacitance1200pFcolerance±20%Yoltage - Rated500Vcomperature CoefficientX7ROperating Temperature-55°C ~ 125°CVaturesHigh TemperatureAutings-Autonsing TypeSurface Mount, MLCC
ackage1210 (3225 Metric)eries-Capacitance1200pFColerance±20%Voltage - Rated500VComperature CoefficientX7ROperating Temperature-55°C ~ 125°CPetaturesHigh TemperatureCatings-Autings-Auting TypeSurface Mount, MLCC
eries-Capacitance1200pFColerance±20%Voltage - Rated500VComperature CoefficientX7ROperating Temperature-55°C ~ 125°CCeaturesHigh TemperatureCatings-ApplicationsHigh ReliabilityCating Type-Mounting TypeSurface Mount, MLCC
Capacitance1200pFSolerance±20%Voltage - Rated500VVemperature CoefficientX7ROperating Temperature-55°C ~ 125°CVeaturesHigh TemperatureValues-Autings-Value Rate-Voltage TypeSurface Mount, MLCC
Polerance±20%Voltage - Rated500VVemperature CoefficientX7ROperating Temperature-55°C ~ 125°CVeaturesHigh TemperatureAttings-Attings-ApplicationsHigh ReliabilityAtting TypeSurface Mount, MLCC
Yoltage - Rated500VYemperature CoefficientX7ROperating Temperature-55°C ~ 125°CYeaturesHigh TemperatureYeatures-Applications-Yeature Rate-Younting TypeSurface Mount, MLCC
Permerature CoefficientX7ROperating Temperature-55°C ~ 125°CPermeraturesHigh TemperaturePatings-Autings-Auting Rate-Auting TypeSurface Mount, MLCC
Operating Temperature-55°C ~ 125°CYeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityYailure Rate-Younting TypeSurface Mount, MLCC
PeaturesHigh TemperatureRatings-ApplicationsHigh Reliabilityrailure Rate-Aounting TypeSurface Mount, MLCC
katings-ApplicationsHigh ReliabilityValue Rate-Aounting TypeSurface Mount, MLCC
ApplicationsHigh ReliabilityGailure Rate-Aounting TypeSurface Mount, MLCC
Pailure Rate -   Aounting Type Surface Mount, MLCC
Aounting Type Surface Mount, MLCC
ackage / Case 1210 (3225 Metric)
ize / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)
Height - Seated (Max) -
Thickness (Max)     0.079" (2.00mm)
ead Spacing -
ead Style -
Report errors?

#### 1210J5000122MDT Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## 1210J5000122MDT Payment Methods





If you have any question about 1210J5000122MDT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com