

1210Y0160220GFR

1210Y0160220GFR Information

Contract service costs have	 1210Y0160220GFR Knowles Syfer Capacitors Ceramic Capacitors CAP CER 22PF 16V C0G/NP0 1210 1210 (3225 Metric) For the pricing/inventory/lead time, please contact		
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a	Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1210Y0160220GFR Specifications

AnaufacturerKnowles SyferCategoryCapacitorsCaranic CapacitorsCeranic CapacitorsPackage1210 (3225 Metric)SeriesFlexiCap?Capacitance22pFColerance±2%Voltage - Rated16VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CVerturesHigh TemperatureValues-Applications-ApplicationsSurface Mount, MLCCValues210 (3225 Metric)Values1210 (3225 Metric)Values1210 (3225 Metric)Values0.126" L x 0.098" W (3.20mm x 2.50mm)		
CategoryCapacitorsCategoryCeramic CapacitorsCacade1210 (3225 Metric)Package1210 (3225 Metric)BeriesFlexiCap?Capacitance22pFColerance±2%Yoltage - Rated16VComperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CPackagesHigh TemperatureRatings-ApplicationsHigh ReliabilityPackage / CaseSurface Mount, MLCCPackage / Case1210 (3225 Metric)Bize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Manufacturer Part Number	1210Y0160220GFR
Ceramic CapacitorsPackage1210 (3225 Metric)PackageFlexiCap?Capacitance22pFPolerance±2%Voltage - Rated16VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CVeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityValuer Rate-Voltage YaseSurface Mount, MLCCPackage / Case1210 (3225 Metric)Bize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Manufacturer	Knowles Syfer
Package1210 (3225 Metric)BeriesFlexiCap?Capacitance22pFTolerance±2%Yoltage - Rated16VCong, NP0-55°C ~ 125°COperating Temperature-55°C ~ 125°CBeatings-ApplicationsHigh ReliabilityFailure Rate-Youting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Bize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Category	Capacitors
KeriesFlexiCap?Capacitance22pFColerance±2%Voltage - Rated16VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilitySailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)		Ceramic Capacitors
Capacitance22pFColerance±2%Yoltage - Rated16VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilitySailure Rate-Younting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Package	1210 (3225 Metric)
Polerance±2%Polarance16VCongon PolaranceCOG, NPOOperating Temperature-55°C ~ 125°COperating Temperature-55°C ~ 125°CSeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityGailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Series	FlexiCap?
AddressAddressAddress16VComperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CGeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityGailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Capacitance	22pF
Comperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Tolerance	±2%
Deperating Temperature-55°C ~ 125°CGeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityGalure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Voltage - Rated	16V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Temperature Coefficient	COG, NP0
Ratings-ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Bize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Features	High Temperature
Failure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Ratings	-
Aounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)	Applications	High Reliability
Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)	Failure Rate	-
Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)	Mounting Type	Surface Mount, MLCC
	Package / Case	1210 (3225 Metric)
	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
leight - Seated (Max) -	Height - Seated (Max)	-
Chickness (Max) 0.079" (2.00mm)	Thickness (Max)	0.079" (2.00mm)
Lead Spacing -	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

1210Y0160220GFR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1210Y0160220GFR Payment Methods





If you have any question about 1210Y0160220GFR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com