

1210Y0250272GFT

1210Y0250272GFT Information

Heisener.com	 1210Y0250272GFT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 2700PF 25V C0G/NP0 1210 1210 (3225 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1210Y0250272GFT Specifications

ManufacturerKnowles SyferCapacitorsCapacitorsPackageCaranic CapacitorsPackage1210 (3225 Metric)SeriesFlexiCap?Capacitance2700pFFolerance25%Voltage - RatedS00 NP0Poperature CoefficientC0G, NP0Operating Temperature55°C ~ 125°CPackageHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rated-Voluting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126° L x 0.098° W (3.20mm x 2.50mm)Hight - Seated (Max)0.079° (2.00mm)		
CategoryCapacitorsCaranic CapacitorsPackage1210 (3225 Metric)SeriesFlexiCap?Capacitance2700pFColgacitance±2%Voltage - Rated25VPemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CPackageHigh TemperaturePackage-ApplicationsHigh ReliabilityFailure Rate-Package / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Hight - Seated (Max)-Chickness (Max)0.079" (2.00mm)	Manufacturer Part Number	1210Y0250272GFT
Ceramic CapacitorsPackage1210 (3225 Metric)SeriesFlexiCap?Capacitance2700pFFolerance±2%Voltage - Rated25VFomperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Package / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.079" (2.00mm)	Manufacturer	Knowles Syfer
Package1210 (3225 Metric)SeriesFlexiCap?Capacitance2700pFFolerance±2%Voltage - Rated25VFemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Package / CaseSurface Mount, MLCCPackage / Case0.126° L x 0.098° W (3.20mm x 2.50mm)Size / Dimension0.79° (2.00mm)	Category	Capacitors
SeriesFlexiCap?Capacitance2700pFColerance±2%Voltage - Rated25VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Package / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)High reserved (Max)0.079" (2.00mm)		Ceramic Capacitors
Capacitance2700pFFolerance±2%Folerance±2%Voltage - Rated25VFemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Package / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Chickness (Max)0.079" (2.00mm)	Package	1210 (3225 Metric)
Folerance±2%Folerance55VFemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureFeatures-Applications-Applications TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.079" (2.00mm)	Series	FlexiCap?
Voltage - Rated25VFemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureFeatures-Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Chickness (Max)0.079" (2.00mm)	Capacitance	2700pF
Femperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.079" (2.00mm)	Tolerance	±2%
Derating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Fhickness (Max)0.079" (2.00mm)	Voltage - Rated	25V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Finkenss (Max)0.079" (2.00mm)	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Fhickness (Max)0.079" (2.00mm)	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Fhickness (Max)0.079" (2.00mm)	Features	High Temperature
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm)	Applications	High Reliability
Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm)	Failure Rate	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm)	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)	Package / Case	1210 (3225 Metric)
Chickness (Max) 0.079" (2.00mm)	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
	Height - Seated (Max)	-
- ead Spacing	Thickness (Max)	0.079" (2.00mm)
	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

1210Y0250272GFT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1210Y0250272GFT Payment Methods



If you have any question about 1210Y0250272GFT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com