



#### 1210Y0250332JFR Information

Heisener.com

Part Number 1210Y0250332JFR
Manufacturer Knowles Syfer
Category Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 3300PF 25V C0G/NP0 1210

**Package** 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1210Y0250332JFR Specifications

Manufacturer Part Number1210Y0250332JFRManufacturerKnowles SyferCategoryCapacitorsPackage1210 (3225 Metric)SeriesFlexiCap?Capacitance3300pFTolerance±5%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCC		
Category Capacitors  Package 1210 (3225 Metric) Series FlexiCap? Capacitance 3300pF  Tolerance ±5% Voltage - Rated 25V  Temperature Coefficient Cog, NP0 Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate Mounting Type Surface Mount, MLCC	Manufacturer Part Number	1210Y0250332JFR
Ceramic CapacitorsPackage1210 (3225 Metric)SeriesFlexiCap?Capacitance3300pFTolerance±5%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCC	Manufacturer	Knowles Syfer
Package 1210 (3225 Metric)  Series FlexiCap?  Capacitance 3300pF  Tolerance ±5%  Voltage - Rated 25V  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features High Temperature  Ratings -  Applications High Reliability  Failure Rate -  Mounting Type Surface Mount, MLCC	Category	Capacitors
Series FlexiCap? Capacitance 3300pF Tolerance ±5%  Voltage - Rated 25V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC		Ceramic Capacitors
Capacitance 3300pF  Tolerance ±5%  Voltage - Rated 25V  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features High Temperature  Ratings -  Applications High Reliability  Failure Rate -  Mounting Type Surface Mount, MLCC	Package	1210 (3225 Metric)
Tolerance ±5%  Voltage - Rated 25V  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features High Temperature  Ratings -  Applications High Reliability  Failure Rate -  Mounting Type Surface Mount, MLCC	Series	FlexiCap?
Voltage - Rated  25V  Temperature Coefficient  COG, NP0  Operating Temperature  -55°C ~ 125°C  Features  High Temperature  Ratings  - Applications  High Reliability  Failure Rate  Mounting Type  Surface Mount, MLCC	Capacitance	3300pF
Temperature Coefficient  COG, NPO  Operating Temperature  -55°C ~ 125°C  Features  High Temperature  Ratings  -  Applications  High Reliability  Failure Rate  -  Mounting Type  Surface Mount, MLCC	Tolerance	±5%
Operating Temperature -55°C ~ 125°C  Features High Temperature  Ratings -  Applications High Reliability  Failure Rate -  Mounting Type Surface Mount, MLCC	Voltage - Rated	25V
Features High Temperature  Ratings - Applications High Reliability  Failure Rate - Mounting Type Surface Mount, MLCC	Temperature Coefficient	C0G, NP0
Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC	Operating Temperature	-55°C ~ 125°C
Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC	Features	High Temperature
Failure Rate - Mounting Type Surface Mount, MLCC	Ratings	-
Mounting Type Surface Mount, MLCC	Applications	High Reliability
	Failure Rate	-
	Mounting Type	Surface Mount, MLCC
Package / Case 1210 (3225 Metric)	Package / Case	1210 (3225 Metric)
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Height - Seated (Max) -	Height - Seated (Max)	-
Thickness (Max) 0.079" (2.00mm)	Thickness (Max)	0.079" (2.00mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

### 1210Y0250332JFR Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 1210Y0250332JFR Payment Methods



















## 1210Y0250332JFR Shipping Methods













If you have any question about 1210Y0250332JFR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com