



1210Y0250822JXR Information

Heisener.com

1210Y0250822JXR Part Number Manufacturer Knowles Syfer Category

Capacitors

Ceramic Capacitors Description CAP CER 8200PF 25V X7R 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1210Y0250822JXR Specifications

Manufacturer Part Number 1210Y0250822JXR Manufacturer Knowles Syfer Category Capacitors Package 1210 (3225 Metric) Series FlexiCap? Capacitance 8200pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package 1210 (3225 Metric) Series FlexiCap? Capacitance 8200pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1210Y0250822JXR
Package 1210 (3225 Metric) Series FlexiCap? Capacitance 8200pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1210 (3225 Metric) Series FlexiCap? Capacitance 8200pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 8200pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 8200pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Package	1210 (3225 Metric)
Tolerance ±5% Voltage - Rated 25V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Series	FlexiCap?
Voltage - Rated25VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Capacitance	8200pF
Temperature Coefficient ATR (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style XTR (2R1) ATR (2R) ATR	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Voltage - Rated	25V
Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R (2R1)
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.079" (2.00mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1210Y0250822JXR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1210Y0250822JXR Payment Methods



















1210Y0250822JXR Shipping Methods













If you have any question about 1210Y0250822JXR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com