

# 1210Y1000333KDR

lest a Quote

### 1210Y1000333KDR Information

Heisener.com	Part Number	1210Y1000333KDR		
	Manufacturer	Knowles Syfer		16.
	Category	Capacitors Ceramic Capacitors	8	2
	Description	CAP CER 0.033UF 100V X7R 1210	- <b>S</b>	ā
	Package	1210 (3225 Metric)		i.
		For the pricing/inventory/lead time, please contact us		
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Re	que

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# 1210Y1000333KDR Specifications

Manufacturer Part Number   1210Y1000333KDR     Manufacturer   Knowles Syfer     Category   Capacitors     Ceramic Capacitors   Ceramic Capacitors     Package   1210 (3225 Metric)     Series   FlexiCap?     Capacitance   0.033µF     Tolerance   ±10%     Voltage - Rated   0.00V     Temperature Coefficient   078 Capacitance     Operating Temperature   55°C ~ 125°C     Features   High Temperature     Applications   High Reliability     Applications   Surface Mount, MLCC     Package / Case   1210 (3225 Metric)     Size / Dimension   0.126°L x 0.098°W (3.20mm x 2.50mm)     High Seated (Max)   -     Thickness (Max)   0.079° (2.00mm)		
CapacitorsPackage1210 (3225 Metric)SeriesFlexiCap?Capacitance0.033µFColarance±10%Voltage - Rated100VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case120 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Hight - Seated (Max)-Hight - Seated (Max)-Hight - Seated (Max)-Hight - Seated (Max)-Hight - Seated (Max)-Lead Spacing-Lead Style-Lead Style-Lead Style-Lead Style-Lead Style-Lead Style-State Case-Lead Style-Lead Style <t< td=""><td>Manufacturer Part Number</td><td>1210Y1000333KDR</td></t<>	Manufacturer Part Number	1210Y1000333KDR
Ceranic CapacitorsPackage1210 (3225 Metric)SeriesFlexiCap?Capacitance0.033µFTolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Applications-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension-Hight - Stated (Max)-Hight - Stated (Max)-Hight - Stated (Max)-Lead Spacing-Lead Style-Lead Style-	Manufacturer	Knowles Syfer
Package1210 (3225 Metric)SeriesFlexiCap?Capacitance0.033µFTolerance±10%Voltage - Rated000VTemperature CoefficientX7ROperating Temperature55°C ~ 125°CFeaturesHigh TemperatureApplications-ApplicationsSurface Mount, MLCCNourting Type0.126°L x 0.098°W (3.20mm x 2.50mm)Size / Dimension0.126°L x 0.098°W (3.20mm x 2.50mm)Height - Seated (Max)0.07°( 0.00mm)Lead Spacing-Lead Style-Lead Style-Street Street S	Category	Capacitors
SeriesFlexiCap?Capacitance0.033µFTolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.126° L x 0.098° W (3.20mm x 2.50mm)High T- Seated (Max)-Thickness (Max)0.079° (2.00mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance   0.033µF     Tolerance   ±10%     Voltage - Rated   100V     Temperature Coefficient   X7R     Operating Temperature   55°C ~ 125°C     Features   High Temperature     Atings   -     Applications   High Reliability     Failure Rate   -     Mounting Type   Surface Mount, MLCC     Size / Dimension   1016325 Metrico     Hight - Seated (Max)   -     Thickness (Max)   0.079° (2.00mm)     Lead Spacing   -     Lead Style   -	Package	1210 (3225 Metric)
Tolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)High Seated (Max)-Lead Spaing0.079" (2.00mm)Lead Style-State Style-Lead Style-State Style-State Style-Style	Series	FlexiCap?
Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFaiture Rate-Mounting TypeSurface Mount, MLCCPackage / Case1010 (3225 Metric)Size / Dimension-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing0.079" (2.00mm) (2.00m	Capacitance	0.033µF
Temperature CoefficientX7ROperating Temperature-5°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126° L x 0.098° W (3.20mm x 2.50mm)Hight - Seated (Max)0.079° (2.00mm)Lead Spacing-Lead Style-Lead Style-Street Compension-Street Com	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Voltage - Rated	100V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Temperature Coefficient	X7R
Ratings-Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Features	High Temperature
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Applications	High Reliability
Package / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)   Height - Seated (Max) -   Thickness (Max) 0.079" (2.00mm)   Lead Spacing -   Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.079" (2.00mm)   Lead Spacing -   Lead Style -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.079" (2.00mm)
-	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### 1210Y1000333KDR Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## 1210Y1000333KDR Payment Methods



If you have any question about 1210Y1000333KDR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com