



1210Y5000103JDR Information

Heisener.com

Part Number 1210Y5000103JDR
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 10000PF 500V X7R 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1210Y5000103JDR Specifications

Manufacturer Part Number 1210Y5000103JDR Manufacturer Knowles Syfer Category Capacitors Package 1210 (3225 Metric) Series FlexiCap? Capacitance 10000pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -		
Category Capacitors Package 1210 (3225 Metric) Series FlexiCap? Capacitance 10000pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1210Y5000103JDR
Package 1210 (3225 Metric) Series FlexiCap? Capacitance 10000pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1210 (3225 Metric) Series FlexiCap? Capacitance 10000pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 10000pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 10000pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Package	1210 (3225 Metric)
Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Series	FlexiCap?
Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Capacitance	10000pF
Temperature Coefficient ATR Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Voltage - Rated	500V
Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Features	High Temperature
Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Applications	High Reliability
Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.079" (2.00mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1210Y5000103JDR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1210Y5000103JDR Payment Methods





















1210Y5000103JDR Shipping Methods













If you have any question about 1210Y5000103JDR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com