

122-13-324-41-801000

122-13-324-41-801000 Information

Heisener.com	 122-13-324-41-801000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 24POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



122-13-324-41-801000 Specifications

Manufacturer Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors Package - Series 122 Type DIP, 0.3" (7.62mm) Row Spacing Number of Positions or Pins (Grid) 24 (2 x 12) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Contact Finish Thickness - Mating Beryllium Copper Mounting Type Through Hole Features Open Frame, Decoupling Capacitor Pitch - Post Gold Contact Finish Thickness - Post Gold Contact Finish Thickness - Post Open Frame, Decoupling Capacitor Pitch - Post Olo0" (2.54mm) Contact Finish Thickness - Post Gold Contact Finish Thickness - Post Gold Contact Finish Thickness - Post Boy Contact Finish Thickness - Post Opin (0.25µm) Contact Finish Thickness - Post Boly Contact Material - Post Brass Alloy Contact Material - Post Polycyclo			
CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackageSeriesSeries122YpeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperPrough HoleContact Material - MatingOpen Frame, Decoupling CapacitorPeturesOpen Frame, Decoupling CapacitorPitch - PostContact Finish Thickness - PostI0µin (0.25µm)Contact Material - PostContact Finish Thickness - PostI0µin (0.25µm)Contact Material - PostContact Finish Thickness - PostI0µin (0.25µm)Contact Material - PostContact Material - PostContact Finish Thickness - PostContact Finish Thickness - PostContact Material - Post <trt< td=""><td>Manufacturer Part Number</td><td>122-13-324-41-801000</td><td></td></trt<>	Manufacturer Part Number	122-13-324-41-801000	
NumberSockets for ICs, TransistorsPackage-Series122TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - PostBitlin (0.25µm)Contact Finish Thickness - PostGoldContact Finish Thickness - PostOpen (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series122TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish - PostGoldContact Finish Thickness - PostIoµin (0.25µm)Contact Finish Thickness - PostBrass AlloyContact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
Series122TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post10µin (0.25µm)Contact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C		Sockets for ICs, Transistors	
Type DIP, 0.3" (7.62mm) Row Spacing Number of Positions or Pins (Grid) 24 (2 x 12) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Contact Material - Mating Beryllium Copper Mounting Type Through Hole Features Open Frame, Decoupling Capacitor Termination Wire Wrap Pitch - Post 0.100" (2.54mm) Contact Finish Thickness - Post Old Contact Finish Thickness - Post 0.100" (2.54mm) Contact Finish Thickness - Post 0.100" (2.54mm) Contact Finish Thickness - Post 0.100" (2.54mm) Contact Finish Thickness - Post 10µin (0.25µm) Contact Finish Thickness - Post 10µin (0.25µm) Contact Material - Post Brass Alloy Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester Operating Temperature -55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostGoldContact Material - PostHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Series	122	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Туре	DIP, 0.3" (7.62mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post10µin (0.25µm)Contact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	24 (2 x 12)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Finish Thickness - Post9rass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
TerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10μin (0.25μm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Features	Open Frame, Decoupling Capacitor	
Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Termination	Wire Wrap	
Contact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Gold	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	10µin (0.25µm)	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Report errors?	Operating Temperature	-55°C ~ 125°C	
			Report errors?

122-13-324-41-801000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

122-13-324-41-801000 Payment Methods WIRE transfer PayPal Methods 122-13-324-41-801000 Shipping Methods



If you have any question about 122-13-324-41-801000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com