

122-13-640-41-001000

122-13-640-41-001000 Information

Heisener.com Statisterverstatt her	Part Number Manufacturer Category Description Package	122-13-640-41-001000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 40POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



122-13-640-41-001000 Specifications

Manufacturer Part Number122-13-640-41-001000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsBackage-Package-Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Mounting TypeBeryllium CopperMounting TypeOpen FrameFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - PostOin (0.76µm)Forture Finish - PostOpen FrameContact Finish - PostOin (2.54mm)Contact Finish - PostOil (2.54mm)Contact Finish			
CategoryConnectsCategoryConnects, InterconnectsPackage-Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeBeryllium CopperMounting TypeOpen FramePitch - Post0.100" (2.54mm)FeaturesOpen FrameOpen Frame100" (2.54mm)Contact Finish - Nating60ldContact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameOpen Frame0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - PostJujin (0.25µm)Contact Finish Thickness - PostJujin (0.25µm)Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Manufacturer Part Number	122-13-640-41-001000	
Sockets for ICs, TransistorsPackage-Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - NotUire WrapPitch - PostGoldContact Finish PostGoldContact Finish Thickness - PostHolin (0.25µm)Contact Finish Thickness - PostI0µin (0.25µm)Contact Finish Thickness - PostBras AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm) Annot Contact Finish - MatingContact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Finish - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFreminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish - PostGoldContact Finish - PostBers AlloyHousing MaterialPosc Coloce Competention (Posc), Polyester	Category	Connectors, Interconnects	
Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBras AlloyHousing MaterialPolycyclohexylenedimethylene Terepthtalate (PCT), Polyester		Sockets for ICs, Transistors	
TypeDIP, 0.6" (15.24mm) Row SpacingTypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - PostGoldContact Material - Post10µin (0.25µm)Housing MaterialBrass Alloy	Package	-	
Number of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Series	122	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Finish Thickness - Post10µin (0.25µm)Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Туре	DIP, 0.6" (15.24mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post10µin (0.25µm)Contact Finish - PostBass AlloyHousing Material - PostBrass Alloy	Number of Positions or Pins (Grid)	40 (2 x 20)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylene Terephthalate (PCT), Polyester	Contact Material - Mating	Beryllium Copper	
TerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Features	Open Frame	
Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Termination	Wire Wrap	
Contact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish - Post	Gold	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish Thickness - Post	10µin (0.25µm)	
	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Operating Temperature -55°C ~ 125°C	Operating Temperature	-55°C ~ 125°C	
Report errors ²			Report errors?

122-13-640-41-001000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

122-13-640-41-001000 Payment Methods





If you have any question about 122-13-640-41-001000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com