

122-13-652-41-001000

122-13-652-41-001000 Information

Heisener.com Octation contains here	 122-13-652-41-001000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 52POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



122-13-652-41-001000 Specifications

Manufacturer Part Number122-13-652-41-001000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsSockets for ICs, TransistorsSockets for ICs, TransistorsPackage-Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)52 (2 x 26)Pitch - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)FeaturesOpen FrameFortinish - PostGoldContact Finish - PostGoldContact Finish - PostGoldManuting TypeMille MatingPitch - PostGoldContact Finish - PostGoldContact Finish Thickness - PostGoldContact Finish Thickness - PostStas Alloy			
CategoryConnectors, InterconnectsPackage-Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)52 (2 x 26)Pitch - Mating0.100" (2.54mm)Contact Finish - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - PostGoldContact Finish - PostOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)	Manufacturer Part Number	122-13-652-41-001000	
Sockets for ICs, TransistorsPackage-Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)52 (2 x 26)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - Post10µin (0.25µm)	Manufacturer	Mill-Max Manufacturing Corp.	
Package.Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)52 (2 x 26)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBerylium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - PostGoldContact Finish - Post0.100" (2.54mm)Contact Finish - Post10µin (0.25µm)	Category	Connectors, Interconnects	
Series122TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)52 (2 x 26)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostDipin (0.25µm)Contact Finish - PostGold		Sockets for ICs, Transistors	
TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)52 (2 x 26)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - Post10µin (0.25µm)	Package	-	
Number of Positions or Pins (Grid)52 (2 x 26)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish - PostGoldContact Finish - PostI0µin (0.25µm)	Series	122	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Туре	DIP, 0.6" (15.24mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostJujin (0.25µm)	Number of Positions or Pins (Grid)	52 (2 x 26)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Contact Material - Mating	Beryllium Copper	
TerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)	Features	Open Frame	
Contact Finish - PostGoldContact Finish Thickness - Post10μin (0.25μm)	Termination	Wire Wrap	
Contact Finish Thickness - Post 10µin (0.25µm)	Pitch - Post	0.100" (2.54mm)	
	Contact Finish - Post	Gold	
Contact Material - Post Brass Allov	Contact Finish Thickness - Post	10µin (0.25µm)	
	Contact Material - Post	Brass Alloy	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C	
Report errors			Report errors?

122-13-652-41-001000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

122-13-652-41-001000 Payment Methods





If you have any question about 122-13-652-41-001000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com