

123-13-306-41-001000

123-13-306-41-001000 Information

| Heisener.com Othereroceants here | 123-13-306-41-001000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 6POS GOLD - For the pricing/inventory/lead time, please contact | |
|-------------------------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



123-13-306-41-001000 Specifications

| Manufacturer Part Number 123-13-306-41-001000 Manufacturer Mill-Max Manufacturing Corp. Category Connectors, Interconnects Sockets for ICs, Transistors Sockets for ICs, Transistors Package - Series 123 Type DIP, 0.3" (7.62mm) Row Spacing Number of Positions or Pins (Grid) 6 (2 x 3) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Contact Material - Mating Gold Contact Material - Mating Open Frame Peatures Open Frame Contact Finish - Post Gold Contact Finish - Post Olu0" (2.54mm) Contact Finish - Post Open Frame Contact Finish - Post Open Frame Contact Finish - Post Olu0" (2.54mm) Contact Finish Thickness - Post Gold Contact Material - Post Brass Alloy Housing | | | |
|--|------------------------------------|---|----------------|
| CategoryConnectors, Interconnects Sockets for ICs, TransistorsPackage-Series123TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperContact Material - MatingBeryllium CopperPitch - PostOpen FramePitch - Post0.100" (2.54mm)Contact Finish ThicknessGoldContact Finish ThicknesBeryllium CopperContact Material - MatingBeryllium CopperContact Material - MatingOpen FrameContact Finish ThicknesOpen FrameContact Finish - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terepthhalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Manufacturer Part Number | 123-13-306-41-001000 | |
| NumberSockets for ICs, TransistorsPackage-Series123TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - Post6IddContact Finish Thickness - Post10µin (0.25µm)Contact Finish Thickness - PostBeryllium CopperPitch - Post9Juje (2.54mm)Contact Finish Thickness - PostSoldContact Finish Thickness - PostSoldContact Finish Thickness - Post9Juje (0.25µm)Contact Material - PostSerss AlloyHousing MaterialPolycyclohexylenedimethylene Terepthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Manufacturer | Mill-Max Manufacturing Corp. | |
| Package-Series123TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperContact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - PostGoldContact Finish Thickness - PostOpen GrameContact Finish Thickness - PostGoldContact Finish Thickness - PostGoldContact Finish Thickness - PostGoldContact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Category | Connectors, Interconnects | |
| Series 123 Type DIP, 0.3" (7.62mm) Row Spacing Number of Positions or Pins (Grid) 6 (2 x 3) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Contact Material - Mating Beryllium Copper Mounting Type Through Hole Features Open Frame Termination Wire Wrap Pitch - Post 0.100" (2.54mm) Contact Finish Thickness - Post Old Contact Finish Thickness - Post Old Contact Finish Thickness - Post Ioµin (0.25µm) Contact Finish Thickness - Post Olyuin (0.25µm) Contact Material - Post Brass Alloy Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester Operating Temperature -55°C ~ 125°C | | Sockets for ICs, Transistors | |
| TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - PostGoldContact Finish Thickness - PostJ0µin (0.25µm)Contact Finish Thickness - PostI0µin (0.25µm)Contact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterPoperating Temperature-55°C ~ 125°C | Package | - | |
| Number of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - Post10µin (0.25µm)Contact Material - PostI0µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Series | 123 | |
| Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Туре | DIP, 0.3" (7.62mm) Row Spacing | |
| Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post10µin (0.25µm)Contact Finish Thickness - Post10µin (0.25µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Number of Positions or Pins (Grid) | 6 (2 x 3) | |
| Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Pitch - Mating | 0.100" (2.54mm) | |
| Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Contact Finish - Mating | Gold | |
| Mounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Contact Finish Thickness - Mating | 30µin (0.76µm) | |
| FeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Contact Material - Mating | Beryllium Copper | |
| TerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Mounting Type | Through Hole | |
| Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Features | Open Frame | |
| Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Termination | Wire Wrap | |
| Contact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Pitch - Post | 0.100" (2.54mm) | |
| Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Contact Finish - Post | Gold | |
| Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C | Contact Finish Thickness - Post | 10µin (0.25µm) | |
| Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Contact Material - Post | Brass Alloy | |
| | Housing Material | Polycyclohexylenedimethylene Terephthalate (PCT), Polyester | |
| Report errors' | Operating Temperature | -55°C ~ 125°C | |
| | | | Report errors? |

123-13-306-41-001000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

123-13-306-41-001000 Payment Methods WIRE transfer PayPal Wind MoneyGram Alipay: VISA Wise 123-13-306-41-001000 Shipping Methods



If you have any question about 123-13-306-41-001000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com