

# 123-43-314-41-801000

#### 123-43-314-41-801000 Information





**Request a Quote** 

For Reference Only

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 123-43-314-41-801000 Specifications

ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, Interconnects Sockets for ICs, TransistorsPackage-Series123TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - MatingO.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorPerintinionWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post20µin (5.08µm)Contact Finish Thickness - PostSolupin (5.08µm)Contact Finish Thickness - PostSolupin (5.08µm)Contact Finish Thickness - PostSolupin (5.08µm)Contact Material - PostFras AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester			
CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series123TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorPitch - Post0.100" (2.54mm)Contact Finish - MatingSoluin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperContact Finish Thickness - MatingDipen Frame, Decoupling CapacitorContact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSoluin (0.78µm)Contact Finish - PostSoluin (0.78µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Manufacturer Part Number	123-43-314-41-801000	
NumberSockets for ICs, TransistorsPackage-Series123TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series123TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - PostSilon (5.08µm)Contact Finish Thickness - PostSilon (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Category	Connectors, Interconnects	
Series123TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester		Sockets for ICs, Transistors	
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Package	-	
Number of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Series	123	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Туре	DIP, 0.3" (7.62mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HolePeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Number of Positions or Pins (Grid)	14 (2 x 7)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen Frame, Decoupling CapacitorTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Material - Mating	Beryllium Copper	
TerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Features	Open Frame, Decoupling Capacitor	
Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Termination	Wire Wrap	
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish - Post	Tin	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish Thickness - Post	200µin (5.08µm)	
	Contact Material - Post	Brass Alloy	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
	Operating Temperature	-55°C ~ 125°C	
Report errors?			Report errors?

E-mail: salesdept@heisener.com

#### 123-43-314-41-801000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 

If you have any question about 123-43-314-41-801000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com