

123-43-950-41-001000

123-43-950-41-001000 Information

	 123-43-950-41-001000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 50POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



123-43-950-41-001000 Specifications

Manufacturer Mill-Max Manufacturing Corp. Category Connectors, Interconnects Sockets for ICs, Transistors Sockets for ICs, Transistors Package - Series 123 Type DIP, 0.9" (22.86mm) Row Spacing Number of Positions or Pins (Grid) 50 (2 x 25) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating 30µin (0.76µm) Contact Material - Mating Beryllium Copper Mounting Type Through Hole Features Open Frame Pitch - Post 0.100" (2.54mm) Contact Finish - Nating 0.100" (2.54mm) Contact Material - Mating Beryllium Copper Termination Wire Wrap Contact Finish - Post 0.100" (2.54mm) Contact Finish - Post Tin Contact Finish Thickness - Post 20µin (5.08µm) Contact Finish Thickness - Post 20µin (5.08µm) Contact Material - Post Brass Alloy Contact Material - Post Brass Alloy Contact Mat			
CategoryConnectors, Interconnects Sockets for ICs, TransistorsPackage-Series123TypeDIP, 0.9" (22.86mm) Row SpacingNumber of Positions or Pins (Grid)50 (2 x 25)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostOpen FrameContact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSocket Socket Sock	Manufacturer Part Number	123-43-950-41-001000	
Sockets for ICs, TransistorsPackage-Series123TypeDIP, 0.9" (22.86mm) Row SpacingNumber of Positions or Pins (Grid)50 (2 x 25)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostPitcyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series123TypeDIP, 0.9" (22.86mm) Row SpacingNumber of Positions or Pins (Grid)50 (2 x 25)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyContact Material - PostPitcyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
Series123TypeDIP, 0.9" (22.86mm) Row SpacingNumber of Positions or Pins (Grid)50 (2 x 25)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C		Sockets for ICs, Transistors	
TypeDIP, 0.9" (22.86mm) Row SpacingNumber of Positions or Pins (Grid)50 (2 x 25)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid)50 (2 x 25)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Series	123	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Туре	DIP, 0.9" (22.86mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54µm)Contact Finish - Post20µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterGoperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	50 (2 x 25)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
TerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Features	Open Frame	
Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Termination	Wire Wrap	
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Tin	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	200µin (5.08µm)	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Report errors?	Operating Temperature	-55°C ~ 125°C	
			Report errors?

123-43-950-41-001000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about 123-43-950-41-001000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com