

1230-100D-3S Information



For Reference Only

Part Number 1230-100D-3S

Manufacturer TE Connectivity Measurement Specialties

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESSURE

Package 8-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1230-100D-3S Specifications

Manufacturer Category Sensors, Transducers Pressure Sensors, Transducers Package 8-DIP Module Series 1230 Pressure Type Differential Operating Pressure 100 PSI (689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.1% Voltage - Supply Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style Maximum Pressure TE Connectivity Measurement Specialties Sensors, Transducers Pressure Sensors, Transducers Pressure Sensors, Transducers 8-DIP Module 1230 Node Possure Sensors, Transducers 1230 Node Possure Sensors 12		
Category Sensors, Transducers Pressure Sensors, Transducers Package 8-DIP Module Series 1230 Pressure Type Differential Operating Pressure 100 PSI (689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.1% Voltage - Supply Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style Maximum Pressure	Manufacturer Part Number	1230-100D-3S
Pressure Sensors, Transducers Package 8-DIP Module Series 1230 Pressure Type Differential Operating Pressure 100 PSI (689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.1% Voltage - Supply - Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Manufacturer	TE Connectivity Measurement Specialties
Package 8-DIP Module Series 1230 Pressure Type Differential Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.1% Voltage - Supply - Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Category	Sensors, Transducers
Series 1230 Pressure Type Differential Operating Pressure 100 PSI (689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.1% Voltage - Supply - Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)		Pressure Sensors, Transducers
Pressure Type Differential Operating Pressure 100 PSI (689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.1% Voltage - Supply - Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Package	8-DIP Module
Operating Pressure 100 PSI (689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.1% Voltage - Supply - Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Series	1230
Output Type Output Output Output On W ~ 100 mV Accuracy ±0.1% Voltage - Supply - Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style Maximum Pressure 200 PSI (1378.95 kPa)	Pressure Type	Differential
Output $0 \text{ mV} \sim 100 \text{ mV}$ Accuracy $\pm 0.1\%$ Voltage - Supply - Port Size $Male - 0.13'' (3.18 \text{mm}) \text{ Tube, Dual}$ Port Style $Barbless$ Features $Temperature Compensated$ Termination Style PCB Maximum Pressure $200 \text{ PSI } (1378.95 \text{ kPa})$	Operating Pressure	100 PSI (689.48 kPa)
Accuracy ±0.1% Voltage - Supply - Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Output Type	Wheatstone Bridge
Voltage - Supply Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Output	$0 \text{ mV} \sim 100 \text{ mV}$
Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Accuracy	±0.1%
Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Voltage - Supply	-
Features Temperature Compensated Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Port Size	Male - 0.13" (3.18mm) Tube, Dual
Termination Style PCB Maximum Pressure 200 PSI (1378.95 kPa)	Port Style	Barbless
Maximum Pressure 200 PSI (1378.95 kPa)	Features	Temperature Compensated
	Termination Style	PCB
	Maximum Pressure	200 PSI (1378.95 kPa)
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-40°C ~ 125°C
Package / Case 8-DIP Module	Package / Case	8-DIP Module
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

1230-100D-3S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1230-100D-3S Payment Methods





















1230-100D-3S Shipping Methods













If you have any question about 1230-100D-3S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com