

1241.1619.11 Information



For Reference Only

Part Number 1241.1619.11

Manufacturer Schurter Inc.

Category Switches
Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 42V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1241.1619.11 Specifications

Manufacturer Part Number 1241.1619.11 Manufacturer Schurter Inc. Category Switches Package - Series SMS Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 42VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.75mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 11.40mm x 11.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 220gf Ingress Protection IP67 - Dust Tight, Waterproof Features Tactile Feedback		
CategorySwitchesPackage-SeriesSMSCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 42VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical7.75mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline11.40mm x 11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force220gfIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesTactile Feedback	Manufacturer Part Number	1241.1619.11
Package - Series SMS Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 42VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.75mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 11.40mm x 11.40mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - COperating Force 220gf Ingress Protection IP67 - Dust Tight, Waterproof Features Tactile Switches SMS TACTILE Switches SMS SMS SPST-NO SPST-NO Opfator Opfator Standard Outlor Outlage (Nominal) - COperating Force 120gf Ingress Protection Features Tactile Feedback	Manufacturer	Schurter Inc.
Package-SeriesSMSCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 42VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical7.75mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline11.40mm x 11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force220gfIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesTactile Feedback	Category	Switches
Series SMS Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 42VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.75mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 11.40mm x 11.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 220gf Ingress Protection IP67 - Dust Tight, Waterproof Features Tactile Feedback		Tactile Switches
Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 42VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.75mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 11.40mm x 11.40mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 220gf Ingress Protection Features Tactile Feedback	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 42VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.75mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 11.40mm x 11.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 220gf Ingress Protection IP67 - Dust Tight, Waterproof Features Tstandard	Series	SMS
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline 11.40mm x 11.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 42VDC Standard Standard Standard Standard Standard Tomant Style 1.475mm Actuated 1.40mm x 11.40mm 1.40mm 1.40	Circuit	SPST-NO
Actuator Type Surface Mount Actuator Height off PCB, Vertical 7.75mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 11.40mm x 11.40mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 220gf Ingress Protection IP67 - Dust Tight, Waterproof Features Tarmination Surface Mount Standard Standard Standard Surface Mount 7.75mm 7.09ma Non-Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) - Tactile Feedback	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline 11.40mm x 11.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount 7.75mm 7.75mm Top Actuated 1.40mm x 11.40mm In Head Top Actuated Top Actuated Top Actuated Top Actuated	Contact Rating @ Voltage	0.05A @ 42VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 11.40mm x 11.40mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 7.75mm 7.75mm 7.75mm 7.75mm 7.75mm 1.75mm 7.75mm	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 11.40mm x 11.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 1220gf Ingress Protection IP67 - Dust Tight, Waterproof Features Tactile Feedback	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style J Lead Outline 11.40mm x 11.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 220gf Ingress Protection IP67 - Dust Tight, Waterproof Features Tactile Feedback	Actuator Height off PCB, Vertical	7.75mm
Termination Style Outline 11.40mm x 11.40mm Illumination Non-Illuminated - Illumination Type, Color Illumination Voltage (Nominal) Operating Force 1220gf Ingress Protection IP67 - Dust Tight, Waterproof Features Tactile Feedback	Actuator Length, Right Angle	-
Outline 11.40mm x 11.40mm Illumination Non-Illuminated	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force220gfIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesTactile Feedback	Termination Style	J Lead
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force220gfIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesTactile Feedback	Outline	11.40mm x 11.40mm
Illumination Voltage (Nominal)-Operating Force220gfIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesTactile Feedback	Illumination	Non-Illuminated
Operating Force220gfIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesTactile Feedback	Illumination Type, Color	-
Ingress Protection IP67 - Dust Tight, Waterproof Features Tactile Feedback	Illumination Voltage (Nominal)	-
Features Tactile Feedback	Operating Force	220gf
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	Tactile Feedback
		Report errors?

1241.1619.11 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1241.1619.11 Payment Methods





















1241.1619.11 Shipping Methods













If you have any question about 1241.1619.11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com