

125M09C Information

Part Number 125M09C Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 125A 600VAC/250VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









125M09C Specifications

Manufacturer Part Number 125M09C Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series HRC II Fuse Type Cartridge Current Rating 125A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Fuse Type Cartridge Current Rating 125A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge Car	Manufacturer Part Number	125M09C
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesHRC IIFuse TypeCartridgeCurrent Rating125AVoltage Rating - AC600VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesHRC IIFuse TypeCartridgeCurrent Rating125AVoltage Rating - AC600VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Category	Circuit Protection
SeriesHRC IIFuse TypeCartridgeCurrent Rating125AVoltage Rating - AC600VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.496" Dia x 2.559" L (38.00mm x 65.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC600VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 125A 600V 600	Series	HRC II
Voltage Rating - AC Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 250V 250V 260V 260V 260V 260V 260V 260V 260V 26	Current Rating	125A
Response Time - Applications - Electrical, Industrial - Class - Class - Approvals - CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - CROWN ARROWS ARRO	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Voltage Rating - DC	250V
Features - Class - CSA Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Response Time	-
Class - CE, CSA Operating Temperature - Sereking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Approvals	CE, CSA
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.496" Dia x 2.559" L (38.00mm x 65.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.496" Dia x 2.559" L (38.00mm x 65.00mm)
		Report errors?

125M09C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

125M09C Payment Methods





















125M09C Shipping Methods













If you have any question about 125M09C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com