



125NH1M Information

Heisener.com

Part Number 125NH1M Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQUARE 125A 500VAC/250VDC

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









125NH1M Specifications

Manufacturer Part Number 125NH1M Manufacturer Eaton Category Circuit Protection Package Rectangular, Blade Series - Fuse Type Square Current Rating 125A Voltage Rating - AC 500V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 50kA DC Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm) Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating125AVoltage Rating - AC500VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage120kA AC, 50kA DCMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.953" L x 2.047" W x 2.165" H (75.00mm x 55.00mm)	Manufacturer Part Number	125NH1M
Electrical, Specialty Fuses Package Rectangular, Blade Series - Fuse Type Square Current Rating 125A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension Electrical, Specialty Fuses Rectangular, Blade Scries Rectangular, Blade Scries Rectangular, Blade Scries Square Squar	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating125AVoltage Rating - AC500VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage120kA AC, 50kA DCMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating125AVoltage Rating - AC500VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage120kA AC, 50kA DCMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating125AVoltage Rating - AC500VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsVDEOperating Temperature-Breaking Capacity @ Rated Voltage120kA AC, 50kA DCMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Package	Rectangular, Blade
Current Rating 125A Voltage Rating - AC 500V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 50kA DC Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 55.00mm)	Series	-
Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Indicating Class NH Approvals VDE Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 500V 250V 250	Fuse Type	Square
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Current Rating	125A
Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 50kA DC Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Voltage Rating - AC	500V
Applications Electrical, Industrial Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 50kA DC Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Voltage Rating - DC	250V
Features Indicating Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 50kA DC Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Response Time	Fast
Class NH Approvals VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 50kA DC Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage 120kA AC, 50kA DC Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension VDE - Rectangular, Blade 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 120kA AC, 50kA DC Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Class	NH
Breaking Capacity @ Rated Voltage 120kA AC, 50kA DC Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Approvals	VDE
Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Breaking Capacity @ Rated Voltage	120kA AC, 50kA DC
Size / Dimension 2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.953" L x 2.047" W x 2.165" H (75.00mm x 52.00mm x 55.00mm)
		Report errors?

125NH1M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

125NH1M Payment Methods

































If you have any question about 125NH1M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com