

125NH2G-690

125NH2G-690 Information

Heisener.com	Part Number Manufacturer Category Description Package	125NH2G-690 Eaton Circuit Protection Electrical, Specialty Fuses FUSE SQ 125A 690VAC RECTANGULAR Rectangular, Blade For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



125NH2G-690 Specifications

Manufacturer Part Number125NH2G-690ManufacturerEdonCategoryCircuit ProtectionPackageRectanglary FusesPackageRectangulary BladeSeries-Fuse TypeSquareCurrent Rating125AVoltage Rating - DC-Voltage Rating - DC-Sponse TimeBelcrical, IndustrialApplicationsElectrical, IndustrialCarsent Same-Approvals-Operating Temperature-Operating Temperature-Operating Type-Apploxals-Approvals-Approvals-Operating Type-Approvals-Aprovals-Approvals-Apploxals-Approvals-Apploxals-Apploxals-Approvals-Apploxals-		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating125AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialKaturesIndicatingVoltage Rating - Marce-ApplorableElectrical, IndustrialResponse TimeGu (Del Cate)ApprovalsCE, VDEOperating Temperature-AprovalsCE, VDEMounting TypeHolderPackage / CaseRectangulan, BladeSize / Dimension2677" L x 2008" W x 2.480" H (68.00mm x 51.00mm)	Manufacturer Part Number	125NH2G-690
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating125AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurren Rating125AYoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFaturesIndicatingClassNHOperating Temperature-Operating Temperature-Munting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" Lx 2.008" Wx 2.480" H(68.00mmx 5.1.00mmx 6.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating125AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingOlarge NameCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Holder-Preakage / CaseRectangulang BadeSize / DimensionScorr" L x 2.008" W x 2.480" H (68.00mm x 51.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating125AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-HolderFolderProkage / CaseRectanguland, BladeSize / Dimension2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Package	Rectangular, Blade
Current Rating125AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectanguland, BladeSize / Dimension2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Series	-
Voltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangulandSize / Dimension2.677" L x 2.008" W x 2.480" H (c8.00mm x 51.00mm x 63.00mm)	Fuse Type	Square
Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Woltage-Mounting TypeHolderPackage / CaseRectangulandSize / Dimension2.677" L x 2.008" W x 2.480" H (68.000m x 5.100m x 6.000m x 6.000m x 5.000m x 6.000m x 6.00	Current Rating	125A
Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2677" L x 2008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Voltage Rating - AC	690V
ApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,677" L x 2,008" W x 2,480" H (68,00mm x 51,00mm x 63,00mm)	Voltage Rating - DC	-
FeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,677" L x 2,008" W x 2,480" H (68.00mm x 51.00mm x 63.00mm)	Response Time	Fast
ClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Applications	Electrical, Industrial
ApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Class	NH
Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Approvals	CE, VDE
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)
		Report errors?

125NH2G-690 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

125NH2G-690 Payment Methods



If you have any question about 125NH2G-690, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com