

# 126-93-318-41-003000

### 126-93-318-41-003000 Information

Heisener.com	 126-93-318-41-003000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 18POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 126-93-318-41-003000 Specifications

Manufacturer Part Number126-93-318-41-003000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsPackage-Package126TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingSolpin (0.76µm)Mounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Finish - PostOpen FrameFinish - PostDing Open (S.64mm)Finish - Post0.100" (2.54mm)Finish - PostDing Open (S.64mm)Finish - PostOpen FrameFinish - PostDing (S.64mm)Finish - PostSolpin (S.64mm)Finish - PostTin-LeadFinish Thickness - PostTin-LeadFinish			
CategoryConnectors, InterconnectsCategorySockets for ICs, TransistorsPackage-Series126TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Firch - PostDing (D.76µm)Firch - PostOpen FrameContact Finish - Post0.100" (2.54mm)Finish - Post0.100" (2.54mm)Contact Finish - Post0.100 (2.54mm)Contact Finish - Post	Manufacturer Part Number	126-93-318-41-003000	
Sockets for ICs, TransistorsPackage-Series126TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)	Manufacturer	Mill-Max Manufacturing Corp.	
Package.Series126TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBerylium CopperContact Material - MatingDen FrameFeaturesOpen FrameFreminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm) <td>Category</td> <td>Connectors, Interconnects</td> <td></td>	Category	Connectors, Interconnects	
Series126TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSin (Jong (Jo		Sockets for ICs, Transistors	
TypeDIP, 0.3" (7.62mm) Row SpacingTypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - Post20µin (5.08µm)	Package	-	
Number of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish - Post200µin (5.08µm)	Series	126	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish - Post200µin (5.08µm)	Туре	DIP, 0.3" (7.62mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post30µin (5.08µm)	Number of Positions or Pins (Grid)	18 (2 x 9)	
Contact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200μin (5.08μm)	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Contact Material - Mating	Beryllium Copper	
TerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Features	Open Frame	
Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Termination	Wire Wrap	
Contact Finish Thickness - Post200µin (5.08µm)	Pitch - Post	0.100" (2.54mm)	
	Contact Finish - Post	Tin-Lead	
	Contact Finish Thickness - Post	200µin (5.08µm)	
Contact Material - Post Brass Alloy	Contact Material - Post	Brass Alloy	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C	
Report errors			Report errors?

### 126-93-318-41-003000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## 126-93-318-41-003000 Payment Methods





If you have any question about 126-93-318-41-003000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com