



126KXM100M Information



For Reference Only

Part Number 126KXM100M Manufacturer Illinois Capacitor

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 12UF 20% 100V THRU HOLE

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









126KXM100M Specifications

Manufacturer Part Number 126KXM100M Manufacturer Illinois Capacitors Category Capacitors Package Radial, Can Series KXM Capacitance 12µF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 11.0524 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	_	
Category Capacitors Package Radial, Can Series KXM Capacitance 12μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 11.0524 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	126KXM100M
Package Radial, Can Series KXM Capacitance 12μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 11.0524 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Illinois Capacitor
Package Radial, Can Series KXM Capacitance 12µF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 11.0524 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series KXM Capacitance 12μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 11.0524 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 12μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 11.0524 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 11.0524 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	KXM
Voltage - Rated100VESR (Equivalent Series Resistance)11.0524 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency46mA @ 120HzRipple Current - High Frequency-Impedance2.8 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	12μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar -55°C ~ 105°C -008" General Purpose 46mA @ 120Hz -0098" 46mA @ 120Hz -0098" -0098" 10	Voltage - Rated	100V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	11.0524 Ohm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency 46mA @ 120Hz Ripple Current - High Frequency - Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency	Polarization	Polar
Ripple Current - High Frequency Impedance 2.8 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance2.8 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	46mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	2.8 Ohms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

126KXM100M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

126KXM100M Payment Methods



















126KXM100M Shipping Methods













If you have any question about 126KXM100M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com