



## 12FFLSJ40 Information

Heisener.com

Part Number 12FFLSJ40
Manufacturer Eaton

**Category** Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE 12KV 40AMP 3" DIN **Package** Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 12FFLSJ40 Specifications

Manufacturer Part Number12FFLSJ40ManufacturerEatonCategoryCircuit ProtectionBecktrical, Specialty FusesPackageCartridge, Non-StandardSeries*Fuse Type-Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 11.496" L (76.20mm x 292.00mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  Cartridge, Non-Standard  Series  * Fuse Type  Current Rating  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Features  Class  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  Cartridge, Non-Standard  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard  Size / Dimension	Manufacturer Part Number	12FFLSJ40
Electrical, Specialty Fuses  Package Cartridge, Non-Standard  Series Fuse Type - Current Rating Voltage Rating - AC - Voltage Rating - DC - Response Time Applications - Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  * Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  * Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  * Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  * Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  * Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  * Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  * Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  * Cartridge, Non-Standard Size / Dimension  Electrical Special	Manufacturer	Eaton
Package         Cartridge, Non-Standard           Series         *           Fuse Type         -           Current Rating         -           Voltage Rating - AC         -           Voltage Rating - DC         -           Response Time         -           Applications         -           Features         -           Class         -           Approvals         -           Operating Temperature         -           Breaking Capacity @ Rated Voltage         -           Mounting Type         Holder           Package / Case         Cartridge, Non-Standard           Size / Dimension         3.000" Dia x 11.496" L (76.20mm x 292.00mm)	Category	Circuit Protection
Series * Fuse Type Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Size / Dimension  **Standard Size / Dimension  **Standard *		Electrical, Specialty Fuses
Fuse Type Current Rating - Voltage Rating - AC Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension - Current Rating	Package	Cartridge, Non-Standard
Current Rating  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Features  Class  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension	Series	*
Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Features  - Class  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  -  Voltage Rating - AC  -  Approvals  -  Class  Cartridge, Non-Standard  Size / Dimension  -  Size / Dimension  -  Cartridge, Non-Standard  Size / Dimension  -  Size / Dimension  -  Cartridge, Non-Standard  Size / Dimension	Fuse Type	-
Voltage Rating - DC  Response Time  Applications  -  Class  -  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  -  Class  -  Cartridge, Non-Standard  Size / Dimension	Current Rating	-
Response Time Applications - Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension - Class	Voltage Rating - AC	-
Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 11.496" L (76.20mm x 292.00mm)	Voltage Rating - DC	-
Features - Class - Approvals - Coperating Temperature - Streaking Capacity @ Rated Voltage - Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 11.496" L (76.20mm x 292.00mm)	Response Time	-
Class - Approvals - Coperating Temperature - Streaking Capacity @ Rated Voltage - Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 11.496" L (76.20mm x 292.00mm)	Applications	-
Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 11.496" L (76.20mm x 292.00mm)	Class	-
Breaking Capacity @ Rated Voltage -  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 3.000" Dia x 11.496" L (76.20mm x 292.00mm)	Approvals	-
Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 3.000" Dia x 11.496" L (76.20mm x 292.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 11.496" L (76.20mm x 292.00mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension 3.000" Dia x 11.496" L (76.20mm x 292.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	3.000" Dia x 11.496" L (76.20mm x 292.00mm)
Report errors.		Report errors?

### 12FFLSJ40 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 12FFLSJ40 Payment Methods



















## 12FFLSJ40 Shipping Methods













If you have any question about 12FFLSJ40, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com