

1331-393J Information

Heisener.com

1331-393J Part Number

Manufacturer API Delevan Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 39UH 75MA 7.9 OHM SMD

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1331-393J Specifications

Manufacturer API Delevan Inc. Category Inductors, Coils, Chokes Fixed Inductors Package 2-SMD Series 1331 Type - Material - Core Iron Inductance 39µH Tolerance ±5% Current Rating 75mA Current - Saturation 75mA Shielding Shielded DC Resistance (DCR) 7,9 Ohm Max Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2.SMD Supplier Device Package -	Manufacturer Part Number	1331-393J
Fixed Inductors	Manufacturer	API Delevan Inc.
Package 2-SMD Series 1331 Type - Material - Core Iron Inductance 39μH Tolerance ±5% Current Rating 75mA Current - Saturation 75mA Shielding Shielded DC Resistance (DCR) 7.9 Ohm Max Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Category	Inductors, Coils, Chokes
Series		Fixed Inductors
Type - Material - Core Iron Inductance 39μH Tolerance ±5% Current Rating 75mA Current - Saturation 75mA Shielding Shielded DC Resistance (DCR) 7.9 Ohm Max Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Package	2-SMD
Material - Core Iron Inductance 39μH Tolerance ±5% Current Rating 75mA Current - Saturation 75mA Shielding Shielded DC Resistance (DCR) 7.9 Ohm Max Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Series	1331
Inductance	Туре	-
Tolerance ±5% Current Rating 75mA Current - Saturation 75mA Shielding Shielded DC Resistance (DCR) 7.9 Ohm Max Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Material - Core	Iron
Current Rating 75mA Current - Saturation 75mA Shielding Shielded DC Resistance (DCR) 7.9 Ohm Max Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Inductance	39μΗ
Current - Saturation 75mA Shielding Shielded DC Resistance (DCR) 7.9 Ohm Max Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Tolerance	±5%
Shielding DC Resistance (DCR) 7.9 Ohm Max Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package -	Current Rating	75mA
DC Resistance (DCR) Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package 7.9 Ohm Max 8 2.5MHz Frequency - Self Resonant 19MHz - Joseph Company C	Current - Saturation	75mA
Q @ Freq 42 @ 2.5MHz Frequency - Self Resonant 19MHz Ratings - Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Shielding	Shielded
Frequency - Self Resonant Ratings Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features Mounting Type Surface Mount Package / Case Supplier Device Package -	DC Resistance (DCR)	7.9 Ohm Max
Ratings - Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Q @ Freq	42 @ 2.5MHz
Operating Temperature -55°C ~ 105°C Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Frequency - Self Resonant	19MHz
Frequency - Test 2.5MHz Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Ratings	-
Features - Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Operating Temperature	-55°C ~ 105°C
Mounting Type Surface Mount Package / Case 2-SMD Supplier Device Package -	Frequency - Test	2.5MHz
Package / Case 2-SMD Supplier Device Package -	Features	-
Supplier Device Package -	Mounting Type	Surface Mount
	Package / Case	2-SMD
0.01011 0.11511 71 (7.05 0.00)	Supplier Device Package	-
Size / Dimension 0.313" L x 0.115" W (7.95mm x 2.92mm)	Size / Dimension	0.313" L x 0.115" W (7.95mm x 2.92mm)

Height - Seated (Max)	0.145" (3.68mm)
	Report errors?

1331-393J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1331-393J Payment Methods



















1331-393J Shipping Methods













If you have any question about 1331-393J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com