

## **1393277-6 Information**



For Reference Only

**Part Number** 1393277-6

Manufacturer TE Connectivity AMP Connectors

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY AUTOMOTIVE SPDT 40A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1393277-6 Specifications

Manufacturer Part Number         1393277-6           Manufacturer         TE Connectivity AMP Connectors           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         V23076           Relay Type         Automotive           Coil Type         Non Latching           Coil Current         133.3mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         40A           Switching Voltage         12VDC - Nom           Turn On Voltage (Max)         6.9 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         5ms           Release Time         3ms           Features         Sealed           Mounting Type         Through Hole           Termination Style         PC Pin		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         V23076           Relay Type         Automotive           Coil Type         Non Latching           Coil Current         133.3mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         40A           Switching Voltage         12VDC - Nom           Turn On Voltage (Max)         6.9 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         5ms           Release Time         3ms           Features         Sealed           Mounting Type         Through Hole           Termination Style         PC Pin	Manufacturer Part Number	1393277-6
Package         -           Series         V23076           Relay Type         Automotive           Coil Type         Non Latching           Coil Current         133.3mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         40A           Switching Voltage         12VDC - Nom           Turn On Voltage (Max)         6.9 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         5ms           Release Time         3ms           Features         Sealed           Mounting Type         Through Hole           Termination Style         PC Pin	Manufacturer	TE Connectivity AMP Connectors
Package         -           Series         V23076           Relay Type         Automotive           Coil Type         Non Latching           Coil Current         133.3mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         40A           Switching Voltage         12VDC - Nom           Turn On Voltage (Max)         6.9 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         5ms           Release Time         3ms           Features         Sealed           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
Series         V23076           Relay Type         Automotive           Coil Type         Non Latching           Coil Current         133.3mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         40A           Switching Voltage         12VDC - Nom           Turn On Voltage (Max)         6.9 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         5ms           Release Time         3ms           Features         Sealed           Mounting Type         Through Hole           Termination Style         PC Pin		Power Relays, Over 2 Amps
Relay TypeAutomotiveCoil TypeNon LatchingCoil Current133.3mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)40ASwitching Voltage12VDC - NomTurn On Voltage (Max)6.9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time5msRelease Time3msFeaturesSealedMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current133.3mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)40ASwitching Voltage12VDC - NomTurn On Voltage (Max)6.9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time5msRelease Time3msFeaturesSealedMounting TypeThrough HoleTermination StylePC Pin	Series	V23076
Coil Current133.3mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)40ASwitching Voltage12VDC - NomTurn On Voltage (Max)6.9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time5msRelease Time3msFeaturesSealedMounting TypeThrough HoleTermination StylePC Pin	Relay Type	Automotive
Coil Voltage 12VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 40A  Switching Voltage 12VDC - Nom  Turn On Voltage (Max) 6.9 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 5ms  Release Time 3ms  Features Sealed  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current) 40A  Switching Voltage 12VDC - Nom  Turn On Voltage (Max) 6.9 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 5ms  Release Time 3ms  Features Sealed  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	133.3mA
Contact Rating (Current)  Switching Voltage  12VDC - Nom  Turn On Voltage (Max)  6.9 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  5ms  Release Time  3ms  Features  Sealed  Mounting Type  Through Hole  Termination Style	Coil Voltage	12VDC
Switching Voltage  Turn On Voltage (Max)  6.9 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  5ms  Release Time  3ms  Features  Sealed  Mounting Type  Through Hole  Termination Style	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  6.9 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  5ms  Release Time  3ms  Features  Sealed  Mounting Type  Through Hole  Termination Style  6.9 VDC  1.2 VDC  5ms  7ms  7ms  7ms  7ms  7ms  7ms  7ms	Contact Rating (Current)	40A
Turn Off Voltage (Min)  Operate Time  Sms  Release Time  Sealed  Mounting Type  Through Hole  Termination Style  1.2 VDC  5ms  Sex  Sex  Mounting Type  Through Hole  PC Pin	Switching Voltage	12VDC - Nom
Operate Time 5ms Release Time 3ms Features Sealed Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	6.9 VDC
Release Time 3ms Features Sealed Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Sealed Mounting Type Through Hole Termination Style PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	3ms
Termination Style PC Pin	Features	Sealed
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **1393277-6 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 1393277-6 Payment Methods





















### 1393277-6 Shipping Methods













If you have any question about 1393277-6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com