

1393807-3 Information



For Reference Only

Part Number 1393807-3

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 5A 32V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1393807-3 Specifications

Manufacturer Part Number1393807-3ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesV23154, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.4mACoil Voltage32VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)16 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeatures-Mounting TypeSocketableTermination StylePlug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesV23154, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.4mACoil Voltage32VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)16 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	1393807-3
Package - Series V23154, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 19.4mA Coil Voltage 32VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series V23154, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 19.4mA Coil Voltage 32VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesV23154, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.4mACoil Voltage32VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)16 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 19.4mA Coil Voltage 32VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil Type Non Latching Coil Current 19.4mA Coil Voltage 32VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Series	V23154, AXICOM
Coil Current Coil Voltage 32VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style 19.4mA 19	Relay Type	General Purpose
Coil Voltage 32VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Coil Current	19.4mA
Contact Rating (Current) Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style 5A 125VAC, 150VDC - Max 16 VDC - Max 16 VDC - Socketable Plug In	Coil Voltage	32VDC
Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	125VAC, 150VDC - Max
Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	16 VDC
Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	7.5ms
Mounting Type Socketable Termination Style Plug In	Release Time	3ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

1393807-3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1393807-3 Payment Methods



















1393807-3 Shipping Methods













If you have any question about 1393807-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com