

### 1393812-2 Information

Heisener.com

**Part Number** 1393812-2

Manufacturer TE Connectivity Potter & Brumfield Relays

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 2A 220V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1393812-2 Specifications

| Manufacturer Part Number         1393812-2           Manufacturer         TE Connectivity Potter & Brumfield Relays           Category         Relays           Package         -           Series         V23054, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         8.8mA           Coil Voltage         220VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         125VAC, 150VDC - Max           Turn On Voltage (Max)         79 VDC           Turn Off Voltage (Min)         -           Operate Time         16ms           Release Time         2ms           Features         - |                          |   |
|--|--------------------------|---|
| Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         V23054, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         8.8mA           Coil Voltage         220VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         125VAC, 150VDC - Max           Turn On Voltage (Max)         79 VDC           Turn Off Voltage (Min)         -           Operate Time         16ms           Release Time         2ms           Features         -   | Manufacturer Part Number | 1393812-2                                 |
| Package         -           Series         V23054, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         8.8mA           Coil Voltage         220VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         125VAC, 150VDC - Max           Turn On Voltage (Max)         79 VDC           Turn Off Voltage (Min)         -           Operate Time         16ms           Release Time         2ms           Features         -   | Manufacturer             | TE Connectivity Potter & Brumfield Relays |
| Package         -           Series         V23054, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         8.8mA           Coil Voltage         220VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         125VAC, 150VDC - Max           Turn On Voltage (Max)         79 VDC           Turn Off Voltage (Min)         -           Operate Time         16ms           Release Time         2ms           Features         -   | Category                 | Relays                                    |
| Series V23054, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 8.8mA Coil Voltage 220VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 79 VDC Turn Off Voltage (Min) - Operate Time 16ms Release Time 2ms  |                          | Signal Relays, Up to 2 Amps               |
| Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage220VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)79 VDCTurn Off Voltage (Min)-Operate Time16msRelease Time2msFeatures-  | Package                  | -   |
| Coil Type Non Latching Coil Current 8.8mA Coil Voltage 220VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 79 VDC Turn Off Voltage (Min) - Operate Time 16ms Release Time 2ms Features -  | Series                   | V23054, AXICOM                            |
| Coil Current8.8mACoil Voltage220VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)79 VDCTurn Off Voltage (Min)-Operate Time16msRelease Time2msFeatures-  | Relay Type               | General Purpose                           |
| Coil Voltage 220VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 79 VDC Turn Off Voltage (Min) - Operate Time 16ms Release Time 2ms Features -  | Coil Type                | Non Latching                              |
| Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 125VAC, 150VDC - Max  Turn On Voltage (Max) 79 VDC  Turn Off Voltage (Min) -  Operate Time 16ms  Release Time 2ms  Features -   | Coil Current             | 8.8mA                                     |
| Contact Rating (Current)  Switching Voltage  125VAC, 150VDC - Max  Turn On Voltage (Max)  79 VDC  Turn Off Voltage (Min)  Operate Time  16ms  Release Time  2ms  Features  -   | Coil Voltage             | 220VDC                                    |
| Switching Voltage 125VAC, 150VDC - Max  Turn On Voltage (Max) 79 VDC  Turn Off Voltage (Min) -  Operate Time 16ms  Release Time 2ms  Features -  | Contact Form             | DPDT (2 Form C)                           |
| Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  16ms  Release Time  2ms  Features  -  | Contact Rating (Current) | 2A  |
| Turn Off Voltage (Min)  Operate Time  16ms  Release Time  2ms  Features  -   | Switching Voltage        | 125VAC, 150VDC - Max                      |
| Operate Time 16ms Release Time 2ms Features -  | Turn On Voltage (Max)    | 79 VDC                                    |
| Release Time 2ms Features -  | Turn Off Voltage (Min)   | -   |
| Features -   | Operate Time             | 16ms                                      |
|  | Release Time             | 2ms                                       |
|  | Features                 | -   |
| Mounting Type Socketable   | Mounting Type            | Socketable                                |
| Termination Style Plug In  | Termination Style        | Plug In                                   |
| Report errors?   |                          | Report errors?                            |

### **1393812-2 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 1393812-2 Payment Methods





















### 1393812-2 Shipping Methods













If you have any question about 1393812-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com