

1393812-5 Information

Heisener.com

Part Number 1393812-5

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 110V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1393812-5 Specifications

Manufacturer Part Number 1393812-5 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Signal Relays, Up to 2 Amps Package - Series V23054, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 12mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 53.5 VDC Turn Off Voltage (Min) - Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPackage-SeriesV23054, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)53.5 VDCTurn Off Voltage (Min)-Operate Time16msRelease Time2msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	1393812-5
Package-SeriesV23054, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)53.5 VDCTurn Off Voltage (Min)-Operate Time16msRelease Time2msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series V23054, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 12mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 53.5 VDC Turn Off Voltage (Min) - Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesV23054, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)53.5 VDCTurn Off Voltage (Min)-Operate Time16msRelease Time2msFeatures-Mounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)53.5 VDCTurn Off Voltage (Min)-Operate Time16msRelease Time2msFeatures-Mounting TypeSocketableTermination StylePlug In	Package	-
Coil Type Non Latching Coil Current 12mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 53.5 VDC Turn Off Voltage (Min) - Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style Plug In	Series	V23054, AXICOM
Coil Current Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 53.5 VDC Turn Off Voltage (Min) - Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 53.5 VDC Turn Off Voltage (Min) - Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 53.5 VDC Turn Off Voltage (Min) Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style	Coil Current	12mA
Contact Rating (Current) Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 53.5 VDC Turn Off Voltage (Min) Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style	Coil Voltage	110VDC
Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 53.5 VDC Turn Off Voltage (Min) - Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style 53.5 VDC	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	125VAC, 150VDC - Max
Operate Time 16ms Release Time 2ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	53.5 VDC
Release Time 2ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	16ms
Mounting Type Socketable Termination Style Plug In	Release Time	2ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
	Termination Style	Plug In
Report errors?		Report errors?

1393812-5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1393812-5 Payment Methods



















1393812-5 Shipping Methods













If you have any question about 1393812-5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com