

13AT2 Information



For Reference Only

Part Number 13AT2

Manufacturer Honeywell Sensing and Productivity Solutions

Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 5A 250V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









13AT2 Specifications

Manufacturer Part Number 13AT2 Manufacturer Honeywell Sensing and Productivity Solutions Category Switches Package - Series AT Circuit DPDT Switch Function On-Off-On Current Rating 5A (AC/DC) Voltage Rating - AC 250V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.53mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -		
Category Switches Package - Series AT Circuit DPDT Switch Function On-Off-On Current Rating 5A (AC/DC) Voltage Rating - AC 250V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Type Standard Round Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Manufacturer Part Number	13AT2
Package - Series AT Circuit DPDT Switch Function On-Off-On Current Rating 5A (AC/DC) Voltage Rating - AC 250V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.53mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package - Series AT Circuit DPDT Switch Function On-Off-On Current Rating 5A (AC/DC) Voltage Rating - AC 250V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.53mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Category	Switches
SeriesATCircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating5A (AC/DC)Voltage Rating - AC250VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.53mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress Protection-		Toggle Switches
CircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating5A (AC/DC)Voltage Rating - AC250VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.53mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress Protection-	Package	-
Switch FunctionOn-Off-OnCurrent Rating5A (AC/DC)Voltage Rating - AC250VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.53mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress Protection-	Series	AT
Current Rating 5A (AC/DC) Voltage Rating - AC 250V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.53mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.53mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection 250V 250V 260V 260V	Switch Function	On-Off-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 17.53mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection - 30V Standard Round Non-Illumination Non-Illuminated Non-Illuminated - Circular - 12.40mm Dia	Current Rating	5A (AC/DC)
Actuator Type Standard Round Actuator Length 17.53mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Voltage Rating - AC	250V
Actuator Length 17.53mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Actuator Length	17.53mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection -	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection -	Termination Style	Solder Lug
Ingress Protection -	Panel Cutout Dimensions	Circular - 12.40mm Dia
	Bushing Thread	15/32-32
Features -	Ingress Protection	-
	Features	-
Report errors?		Report errors?

13AT2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

13AT2 Payment Methods


































If you have any question about 13AT2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com