

14-6810-90C Information

Heisener.com

14-6810-90C Part Number Manufacturer Aries Electronics

Category Connectors, Interconnects

Sockets for ICs, Transistors

Description CONN IC DIP SOCKET 14POS GOLD

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









14-6810-90C Specifications

Manufacturer Category Connectors, Interconnects Sockets for ICs, Transistors Package - Series Vertisockets? 800 Type DIP, 0.6" (15.24mm) Row Spacing Number of Positions or Pins (Grid) 14 (2 x 7) Pitch - Mating Contact Finish - Mating Gold Contact Finish Thickness - Mating Beryllium Copper Mounting Type Through Hole, Right Angle, Vertical Features Closed Frame Termination Solder Pitch - Post 0.100" (2.54mm) Contact Finish - Post Tin Contact Finish - Post Tin Contact Finish - Post Contact Finish - Post Post Post Post Post Post Post Post			
Category Connectors, Interconnects Sockets for ICs, Transistors Package - Series Vertisockets? 800 Type DIP, 0.6" (15.24mm) Row Spacing Number of Positions or Pins (Grid) 14 (2 x 7) Pitch - Mating Contact Finish - Mating Gold Contact Finish Thickness - Mating Contact Material - Mating Beryllium Copper Mounting Type Through Hole, Right Angle, Vertical Closed Frame Closed Frame Termination Solder Pitch - Post 0.100" (2.54mm) Contact Finish - Post 0.100" (2.54mm) Contact Finish - Post 0.100" (2.54mm) Contact Finish - Post Double Features Pitch - Post Double Fost Double Finish - Post Pitch - Post Post Double Finish - Post Post Double Finish - Post Post Double Finish - Post Double Finish - Post Post Double Finish - Post Post Post Post Post Post Post Post	Manufacturer Part Number	14-6810-90C	
Sockets for ICs, Transistors Package Series Vertisockets? 800 Type DIP, 0.6" (15.24mm) Row Spacing Number of Positions or Pins (Grid) 14 (2 x 7) Pitch - Mating O.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating Contact Material - Mating Beryllium Copper Mounting Type Through Hole, Right Angle, Vertical Closed Frame Termination Solder Pitch - Post O.100" (2.54mm) Contact Finish - Post Tin Contact Finish Thickness - Post Pitch - Post Through Hole, Right Angle, Vertical Solder Pitch - Post D.100" (2.54mm) Contact Finish - Post Pitch - Post Post Post Post Post Post Post Post	Manufacturer	Aries Electronics	
Package Series Vertisockets? 800 Type DIP, 0.6" (15.24mm) Row Spacing Number of Positions or Pins (Grid) 14 (2 x 7) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating Contact Material - Mating Beryllium Copper Mounting Type Through Hole, Right Angle, Vertical Features Closed Frame Termination Solder Pitch - Post 0.100" (2.54mm) Contact Finish - Post Tin Contact Finish Thickness - Post 200μin (5.08μm) Contact Material - Post Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature	Category	Connectors, Interconnects	
SeriesVertisockets? 800TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, VerticalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200μin (5.08μm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass FilledOperating Temperature-		Sockets for ICs, Transistors	
TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, VerticalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200μin (5.08μm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass FilledOperating Temperature-	Package	-	
Number of Positions or Pins (Grid) Pitch - Mating Contact Finish - Mating Contact Finish Thickness - Mating Contact Material - Mating Beryllium Copper Mounting Type Through Hole, Right Angle, Vertical Features Closed Frame Termination Solder Pitch - Post Contact Finish Thickness - Post Contact Finish Thickness - Post Contact Material - Post Brass Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature	Series	Vertisockets? 800	
Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Contact Material - Mating Beryllium Copper Mounting Type Through Hole, Right Angle, Vertical Features Closed Frame Termination Solder Pitch - Post 0.100" (2.54mm) Contact Finish - Post Tin Contact Finish Thickness - Post 200µin (5.08µm) Contact Material - Post Brass Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature -	Type	DIP, 0.6" (15.24mm) Row Spacing	
Contact Finish - Mating Contact Finish Thickness - Mating Contact Material - Mating Beryllium Copper Mounting Type Through Hole, Right Angle, Vertical Closed Frame Closed Frame Termination Solder Pitch - Post Ontact Finish - Post Tin Contact Finish Thickness - Post Contact Material - Post Brass Housing Material Operating Temperature Gold 30µin (0.76µm) Through Hole, Right Angle, Vertical Closed Frame Closed Frame Trough Hole, Right Angle, Vertical Closed Frame Closed Frame Solder 0.100" (2.54mm) Tin Contact Finish - Post Post Post Post Post Post Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature	Number of Positions or Pins (Grid)	14 (2 x 7)	
Contact Finish Thickness - Mating Contact Material - Mating Beryllium Copper Mounting Type Through Hole, Right Angle, Vertical Closed Frame Termination Solder Pitch - Post Contact Finish - Post Contact Finish Thickness - Post Contact Finish Thickness - Post Contact Material - Post Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature 30µin (0.76µm) Beryllium Copper Through Hole, Right Angle, Vertical Closed Frame Closed Frame 7 Closed Frame \$\text{Closed Frame}\$ \$\text{Closed Frame}\$ \$\text{Closed Frame}\$ \$\text{Tin}\$ \$\text{Contact Finish - Post}\$ Brass Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled	Pitch - Mating	0.100" (2.54mm)	
Contact Material - Mating Mounting Type Through Hole, Right Angle, Vertical Closed Frame Closed Frame Termination Solder Pitch - Post Ontact Finish - Post Tin Contact Finish Thickness - Post Contact Material - Post Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature Beryllium Copper Through Hole, Right Angle, Vertical Closed Frame 200e Trime 0.100" (2.54mm) Tin 200µin (5.08µm) Polyamide (PA46), Nylon 4/6, Glass Filled	Contact Finish - Mating	Gold	
Mounting TypeThrough Hole, Right Angle, VerticalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200μin (5.08μm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass FilledOperating Temperature-	Contact Finish Thickness - Mating	30μin (0.76μm)	
FeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200μin (5.08μm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass FilledOperating Temperature-	Contact Material - Mating	Beryllium Copper	
Termination Solder Pitch - Post 0.100" (2.54mm) Contact Finish - Post Tin Contact Finish Thickness - Post 200μin (5.08μm) Contact Material - Post Brass Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature -	Mounting Type	Through Hole, Right Angle, Vertical	
Pitch - Post 0.100" (2.54mm) Contact Finish - Post Tin Contact Finish Thickness - Post 200μin (5.08μm) Contact Material - Post Brass Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature -	Features	Closed Frame	
Contact Finish - Post Contact Finish Thickness - Post 200µin (5.08µm) Contact Material - Post Brass Housing Material Operating Temperature Tin 200µin (5.08µm) Brass Polyamide (PA46), Nylon 4/6, Glass Filled -	Termination	Solder	
Contact Finish Thickness - Post 200µin (5.08µm) Contact Material - Post Brass Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature -	Pitch - Post	0.100" (2.54mm)	
Contact Material - Post Brass Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature -	Contact Finish - Post	Tin	
Housing Material Polyamide (PA46), Nylon 4/6, Glass Filled Operating Temperature -	Contact Finish Thickness - Post	200μin (5.08μm)	
Operating Temperature -	Contact Material - Post	Brass	
	Housing Material	Polyamide (PA46), Nylon 4/6, Glass Filled	
Report errors?	Operating Temperature	-	
			Report errors?

14-6810-90C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

14-6810-90C Payment Methods



















14-6810-90C Shipping Methods













If you have any question about 14-6810-90C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com