

142.6185.4106

142.6185.4106 Information



Part Number142.6185.4106ManufacturerLittelfuse Inc.CategoryCircuit Protection
FusesDescriptionFUSE AUTOMOTIVE 1A 58VDC BLADEPackageBlade, ATO/ATC
For the pricing/inventory/lead time, please contact
us
Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



142.6185.4106 Specifications

| Manufacturer Part Number142.6185.4106ManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFusesPackageBlade, ATO/ATCSeriesTAC ATO?Fuse TypeAutomotiveCurrent RatingIAVoltage Rating - AC-Voltage Rating - DCS8VPackage / CaseBlade, ATO/ATCMounting TypeBlade, ATO/ATCMounting TypeIderBreaking Capacity @ Rated VoltageIkAMelting I2t2ApprovalscULusOperating Temperature-ColorBlackSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm) | | |
|--|-----------------------------------|---|
| CategoryCircuit ProtectionFusesPackageBlade, ATO/ATCSeriesTAC ATO?Fuse TypeAutomotiveCurrent RatingIAVoltage Rating - AC-Voltage Rating - DC58VResponse TimeBlade, ATO/ATCPackage / CaseBlade, ATO/ATCMounting TypeIAldeBreaking Capacity @ Rated VoltageIAApprovalscULusOperating Temperature-ColorBlackBlackStateBlackStateBlackStateApprovalsBlackBlackStateS | Manufacturer Part Number | 142.6185.4106 |
| FusesPackageBlade, ATO/ATCSeriesTAC ATO?Fuse TypeAutomotiveCurrent RatingIAVoltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1KAMelting I2t2ApprovalscULusOperating Temperature-KolonBlack | Manufacturer | Littelfuse Inc. |
| PackageBlade, ATO/ATCPackageTAC ATO?Fuse TypeAutomotiveCurrent RatingIAVoltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1Melting I2t2ApprovalscULusOperating TemperatureBlackBlackSubsectStateSubsectApprovalsBlackColorBlack | Category | Circuit Protection |
| SeriesTAC ATO?Fuse TypeAutomotiveCurrent RatingIAVoltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1Melting I2t2ApprovalscULusOperating TemperatureBlackBlackStateBlackStateBlackStateOperating TemperatureBlackState< | | Fuses |
| Fuse TypeAutomotiveFuse TypeAutomotiveCurrent RatingIAVoltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated VoltageIkAMelting I2t2ApprovalscULusOperating Temperature-BlackBlack | Package | Blade, ATO/ATC |
| Current RatingIAVoltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1kAMelting I2t2ApprovalscULusOperating Temperature-KolorBlack ATO/ATC | Series | TAC ATO? |
| Voltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated VoltageIkAMelting I2t2ApprovalscULusOperating Temperature-BlackBlackMelting I2tBlackBase-Base | Fuse Type | Automotive |
| Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1kAMelting I2t2ApprovalscULusOperating Temperature-KolorBlack | Current Rating | 1A |
| Response TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1kAMelting I2t2ApprovalscULusOperating Temperature-ColorBlack | Voltage Rating - AC | - |
| Package / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1kAMelting I2t2ApprovalscULusOperating Temperature-ColorBlack | Voltage Rating - DC | 58V |
| Mounting TypeHolderBreaking Capacity @ Rated Voltage1kAMelting I2t2ApprovalscULusOperating Temperature-ColorBlack | Response Time | Fast |
| Breaking Capacity @ Rated Voltage1kAMelting I2t2ApprovalscULusOperating Temperature-ColorBlack | Package / Case | Blade, ATO/ATC |
| Melting I2t2ApprovalscULusOperating Temperature-ColorBlack | Mounting Type | Holder |
| ApprovalscULusOperating Temperature-ColorBlack | Breaking Capacity @ Rated Voltage | 1kA |
| Operating Temperature - Color Black | Melting I2t | 2 |
| Color Black | Approvals | cULus |
| | Operating Temperature | - |
| Size / Dimension 0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm) | Color | Black |
| | Size / Dimension | 0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm) |
| Report e | | Report errors? |

142.6185.4106 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 142.6185.4106, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com