

142.6185.5156

142.6185.5156 Information



Part Number	142.6185.5156	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Fuses	
Description	FUSE AUTOMOTIVE 15A 58VDC BLADE	
Package	Blade, ATO/ATC	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



142.6185.5156 Specifications

Manufacturer Part Number142.6185.5156ManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFusesPackageBlade, ATO/ATCSeriesTAC ATO?Fuse TypeAutomotiveCurrent Rating15AVoltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1KAMelting 12250ApprovalscULusOperating Temperature-ColorBlueMount Superature-ColorDire Att No.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)		
CategoryCircuit ProtectionFusesPackageBlade, ATO/ATCSeriesTAC ATO?Fuse TypeAutonotiveCurrent Rating15AVoltage Rating - AC-Voltage Rating - DCS8VPackage / CaseBlade, ATO/ATCPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated VoltageIAAutonoticS0ApprovalsCULusOperating Temperature-ColorBlueSize / Dimension0.48" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)	Manufacturer Part Number	142.6185.5156
FusesPackageBlade, ATO/ATCSeriesTAC ATO?Fuse TypeAutomotiveCurrent Rating15AVoltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1KAMelting 12t250Operating Temperature-ColorBlueSize / Dimension0,48" L x 0.197" W x 0.520" H (19.00mm x 13.20mm)	Manufacturer	Littelfuse Inc.
PackageBlade, ATO/ATCPackageTAC ATO?SeriesAutomotiveFuse TypeAutomotiveCurrent Rating15AVoltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1KAMelting 12t250ApprovalscULusOperating Temperature-Size / Dimension0/48" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)	Category	Circuit Protection
Series TAC ATO? Fuse Type Autonotive Current Rating 15A Voltage Rating - AC - Voltage Rating - DC 58V Response Time Fast Package / Case Blade, ATO/ATC Mounting Type Holder Breaking Capacity @ Rated Voltage IKA Melting I2t 250 Operating Temperature - Color Blue Size / Dimension 0.748" L x 0.197" W x 0.520" H (19.00mm x 13.20mm)		Fuses
Fuse TypeAutomotiveFuse TypeAutomotiveCurrent Rating15AVoltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1KAMelting 12t250ApprovalscultusOperating Temperature-ColorBlueSize / Dimension0.48" L x 0.197" W x 0.520" H (19.00mm x 13.20mm)	Package	Blade, ATO/ATC
Current Rating15ACurrent Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1kAMelting 12t250ApprovalscULusOperating Temperature-ColorBlueSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)	Series	TAC ATO?
Voltage Rating - AC-Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated Voltage1kAMelting I2t250ApprovalscULusOperating Temperature-ColorBlueSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 13.20mm)	Fuse Type	Automotive
Voltage Rating - DC58VResponse TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated VoltageIkAMelting I2t250ApprovalscULusOperating Temperature-ColorBueSize / Dimension0.488 "L x 0.197 "W x 0.520" H (19.00mm x 5.00mm x 13.20mm)	Current Rating	15A
Response TimeFastPackage / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated VoltageIkAMelting I2t250ApprovalscULusOperating Temperature-ColorBlueSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 13.20mm)	Voltage Rating - AC	-
Package / CaseBlade, ATO/ATCMounting TypeHolderBreaking Capacity @ Rated VoltageIkAMelting I2t250ApprovalscULusOperating Temperature-ColorBlueSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)	Voltage Rating - DC	58V
Mounting TypeHolderBreaking Capacity @ Rated Voltage1kAMelting I2t250ApprovalscULusOperating Temperature-ColorBlueSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 13.20mm)	Response Time	Fast
Breaking Capacity @ Rated VoltageIkAMelting I2t250ApprovalscULusOperating Temperature-ColorBlueSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)	Package / Case	Blade, ATO/ATC
Melting I2t250ApprovalscULusOperating Temperature-ColorBlueSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 13.20mm)	Mounting Type	Holder
ApprovalscULusOperating Temperature-ColorBlueSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 13.20mm)	Breaking Capacity @ Rated Voltage	1kA
Operating Temperature-ColorBlueSize / Dimension0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)	Melting I2t	250
Color Blue Size / Dimension 0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)	Approvals	cULus
Size / Dimension 0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)	Operating Temperature	-
	Color	Blue
Papert artor	Size / Dimension	0.748" L x 0.197" W x 0.520" H (19.00mm x 5.00mm x 13.20mm)
Report enor		Report errors?

142.6185.5156 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

142.6185.5156 Payment Methods WIRE transfer PayPal Methods 142.6185.5156 Shipping Methods Feelex. I Control Tells I Cont

If you have any question about 142.6185.5156, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com