

14281-20PG-300 Information



For Reference Only

Part Number 14281-20PG-300

Manufacturer Conxall/Switchcraft

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 20POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









14281-20PG-300 Specifications

Manufacturer Part Number 14281-20PG-300 Manufacturer Connall/Switchcraft Category Connectors, Interconnects Package - Series Maxi-Con-X? Connector Type Receptacle, Male Pins Number of Positions 20 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut, Flange Termination Solder Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features - Voltage - Rated 600V Current Rating -		
CategoryConnectors, InterconnectsPackage-SeriesMaxi-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions20Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut, FlangeTerminationSolderFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeatures-Voltage - Rated600VCurrent Rating-	Manufacturer Part Number	14281-20PG-300
Package-SeriesMaxi-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions20Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut, FlangeTerminationSolderFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeatures-Voltage - Rated600VCurrent Rating-	Manufacturer	Conxall/Switchcraft
Package-SeriesMaxi-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions20Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut, FlangeTerminationSolderFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeatures-Voltage - Rated600VCurrent Rating-	Category	Connectors, Interconnects
SeriesMaxi-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions20Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut, FlangeTerminationSolderFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeatures-Voltage - Rated600VCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions20Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut, FlangeTerminationSolderFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeatures-Voltage - Rated600VCurrent Rating-	Package	-
Number of Positions20Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut, FlangeTerminationSolderFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeatures-Voltage - Rated600VCurrent Rating-	Series	Maxi-Con-X?
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut, Flange Termination Solder Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features - Voltage - Rated Current Rating	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut, Flange Termination Solder Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features - Voltage - Rated 600V Current Rating	Number of Positions	20
Mounting TypePanel Mount, Bulkhead - Front Side Nut, FlangeTerminationSolderFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeatures-Voltage - Rated600VCurrent Rating-	Shell Size - Insert	-
Termination Solder Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features - Voltage - Rated 600V Current Rating -	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Bayonet Lock Reyed Bayonet Lock Reyed A Gold Seyed Nylon Ontact Finish Odd - Contact Finish - Contact Fin	Mounting Type	Panel Mount, Bulkhead - Front Side Nut, Flange
Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features - Voltage - Rated 600V Current Rating -	Termination	Solder
Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features - Voltage - Rated 600V Current Rating -	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating	Orientation	Keyed
Contact Finish Gold Features - Voltage - Rated 600V Current Rating -	Ingress Protection	Weathertight
Features - Voltage - Rated 600V Current Rating -	Shell Material, Finish	Nylon
Voltage - Rated 600V Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
-	Voltage - Rated	600V
Report errors?	Current Rating	-
		Report errors?

14281-20PG-300 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

14281-20PG-300 Payment Methods





















14281-20PG-300 Shipping Methods













If you have any question about 14281-20PG-300, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com