

### **1442700000 Information**

Heisener.com

For Reference Only

Part Number 1442700000 Manufacturer Weidmuller

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** RSV 1.6 LBF 9 GR 3.2 SN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 1442700000 Specifications

Manufacturer Part Number         1442700000           Manufacturer         Weidmuller           Category         Connectors, Interconnects           Package         -           Series         Omnimate RSV           Connector Type         Receptacle           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         9           Number of Positions Loaded         All           Pitch - Mating         0.197" (5.00mm)           Number of Rows         3           Row Spacing - Mating         0.197" (5.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Latch Holder           Contact Finish - Mating         -           Contact Finish Thickness - Mating         -           Insulation Color         Gray           Insulation Height         0.563" (14.30mm)           Contact Length - Post         0.126" (3.20mm)           Operating Temperature         -20°C ~ 120°C           Material Flammability Rating         UL94 V-0		
Category         Connectors, Interconnects           Package         -           Series         Omnimate RSV           Connector Type         Receptacle           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         9           Number of Positions Loaded         All           Pitch - Mating         0.197" (5.00mm)           Number of Rows         3           Row Spacing - Mating         0.197" (5.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Latch Holder           Contact Finish - Mating         Tin           Contact Finish Thickness - Mating         -           Insulation Color         Gray           Insulation Height         0.563" (14.30mm)           Contact Length - Post         0.126" (3.20mm)           Operating Temperature         -20°C ~ 120°C	Manufacturer Part Number	1442700000
Package-SeriesOmnimate RSVConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions9Number of Positions LoadedAllPitch - Mating0.197" (5.00mm)Number of Rows3Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorGrayInsulation Height0.563" (14.30mm)Contact Length - Post0.126" (3.20mm)Operating Temperature-20°C ~ 120°C	Manufacturer	Weidmuller
Package         -           Series         Omnimate RSV           Connector Type         Receptacle           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         9           Number of Positions Loaded         All           Pitch - Mating         0.197" (5.00mm)           Number of Rows         3           Row Spacing - Mating         0.197" (5.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Latch Holder           Contact Finish - Mating         Tin           Contact Finish Thickness - Mating         -           Insulation Color         Gray           Insulation Height         0.563" (14.30mm)           Contact Length - Post         0.126" (3.20mm)           Operating Temperature         -20°C ~ 120°C	Category	Connectors, Interconnects
SeriesOmnimate RSVConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions9Number of Positions LoadedAllPitch - Mating0.197" (5.00mm)Number of Rows3Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorGrayInsulation Height0.563" (14.30mm)Contact Length - Post0.126" (3.20mm)Operating Temperature-20°C ~ 120°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions9Number of Positions LoadedAllPitch - Mating0.197" (5.00mm)Number of Rows3Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorGrayInsulation Height0.563" (14.30mm)Contact Length - Post0.126" (3.20mm)Operating Temperature-20°C ~ 120°C	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions9Number of Positions LoadedAllPitch - Mating0.197" (5.00mm)Number of Rows3Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorGrayInsulation Height0.563" (14.30mm)Contact Length - Post0.126" (3.20mm)Operating Temperature-20°C ~ 120°C	Series	Omnimate RSV
Style Board to Board or Cable  Number of Positions 9  Number of Positions Loaded All  Pitch - Mating 0.197" (5.00mm)  Number of Rows 3  Row Spacing - Mating 0.197" (5.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Latch Holder  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Gray  Insulation Height 0.563" (14.30mm)  Contact Length - Post 0.126" (3.20mm)  Operating Temperature -20°C ~ 120°C	Connector Type	Receptacle
Number of Positions 9 Number of Positions Loaded All Pitch - Mating 0.197" (5.00mm) Number of Rows 3 Row Spacing - Mating 0.197" (5.00mm) Mounting Type Through Hole Termination Solder Fastening Type Latch Holder Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Gray Insulation Height 0.563" (14.30mm) Contact Length - Post 0.126" (3.20mm) Operating Temperature -20°C ~ 120°C	Contact Type	Female Socket
Number of Positions Loaded Pitch - Mating 0.197" (5.00mm)  Number of Rows 3 Row Spacing - Mating 0.197" (5.00mm)  Mounting Type Through Hole Termination Solder Fastening Type Latch Holder Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color Gray Insulation Height 0.563" (14.30mm) Contact Length - Post 0.126" (3.20mm) Operating Temperature -20°C ~ 120°C	Style	Board to Board or Cable
Pitch - Mating 0.197" (5.00mm)  Number of Rows 3  Row Spacing - Mating 0.197" (5.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Latch Holder  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Gray  Insulation Height 0.563" (14.30mm)  Contact Length - Post 0.126" (3.20mm)  Operating Temperature -20°C ~ 120°C	Number of Positions	9
Number of Rows  Row Spacing - Mating  0.197" (5.00mm)  Mounting Type  Through Hole  Termination  Solder  Fastening Type  Latch Holder  Contact Finish - Mating  Tin  Contact Finish Thickness - Mating  Insulation Color  Gray  Insulation Height  0.563" (14.30mm)  Contact Length - Post  0.126" (3.20mm)  Operating Temperature  -20°C ~ 120°C	Number of Positions Loaded	All
Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorGrayInsulation Height0.563" (14.30mm)Contact Length - Post0.126" (3.20mm)Operating Temperature-20°C ~ 120°C	Pitch - Mating	0.197" (5.00mm)
Mounting Type Through Hole  Termination Solder  Fastening Type Latch Holder  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Gray  Insulation Height 0.563" (14.30mm)  Contact Length - Post 0.126" (3.20mm)  Operating Temperature -20°C ~ 120°C	Number of Rows	3
Termination Solder  Fastening Type Latch Holder  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Gray  Insulation Height 0.563" (14.30mm)  Contact Length - Post 0.126" (3.20mm)  Operating Temperature -20°C ~ 120°C	Row Spacing - Mating	0.197" (5.00mm)
Fastening Type  Contact Finish - Mating  Contact Finish Thickness - Mating  Insulation Color  Gray  Insulation Height  Ontact Length - Post  Operating Temperature  Latch Holder  Tin  Contact Finish Thickness - Mating  - Use of the post of the pos	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Gray Insulation Height 0.563" (14.30mm) Contact Length - Post 0.126" (3.20mm) Operating Temperature -20°C ~ 120°C	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Gray Insulation Height 0.563" (14.30mm) Contact Length - Post 0.126" (3.20mm) Operating Temperature -20°C ~ 120°C	Fastening Type	Latch Holder
Insulation ColorGrayInsulation Height $0.563"$ (14.30mm)Contact Length - Post $0.126"$ (3.20mm)Operating Temperature $-20^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Contact Finish - Mating	Tin
Insulation Height $0.563" (14.30mm)$ Contact Length - Post $0.126" (3.20mm)$ Operating Temperature $-20^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Contact Finish Thickness - Mating	-
Contact Length - Post $0.126" (3.20mm)$ Operating Temperature $-20^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Insulation Color	Gray
Operating Temperature $-20^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Insulation Height	0.563" (14.30mm)
	Contact Length - Post	0.126" (3.20mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-20°C ~ 120°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	Mounting Flange
	Report errors?

### **1442700000 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 1442700000 Payment Methods



















## 1442700000 Shipping Methods













If you have any question about 1442700000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com