

1445322-5

1445322-5 Information

Heisener.com	Part Number Manufacturer Category Description Package	1445322-5 TE Connectivity AMP Connectors Connectors, Interconnects Circular Connectors CONN PLUG CPC 5POS SOLDER CUP	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1445322-5 Specifications

ManufacturerTE Connectivity AMP ConnectorsCategoryConnectors, InterconnectsPackage-Package-SeriesMicro CPCConnector TypePlug, Female SocketsNumber of Positions5Shell Size - InsertM9.5Munting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - RatedSpring P		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMicro CPCConnector TypePlug, Female SocketsNumber of Positions5Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionThermoplasticShell Material, FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Manufacturer Part Number	1445322-5
Circular ConnectorsPackage-SeriesMicro CPCConnector TypePlug, Female SocketsNumber of Positions5Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Manufacturer	TE Connectivity AMP Connectors
Package-SeriesMicro CPCConnector TypePlug, Female SocketsNumber of Positions5Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeSolder CupFastening TypeLatch LockOrientationH95 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Category	Connectors, Interconnects
SeriesMicro CPCConnector TypePlug, Female SocketsNumber of Positions5Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationIP65 - Dust Tight, Water ResistantIngress ProtectionThermoplasticShell Material, FinishThermoplasticContact FinishSpring ProbeFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions5Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionThermoplasticShell Material, FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Package	-
Number of Positions5Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Series	Micro CPC
Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishGoldContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionMeroplasticShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Number of Positions	5
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Shell Size - Insert	M9.5
TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Shell Size, MIL	-
Fastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Mounting Type	Free Hanging (In-Line)
OrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Termination	Solder Cup
Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Fastening Type	Latch Lock
Shell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Orientation	Keyed
Contact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Ingress Protection	IP65 - Dust Tight, Water Resistant
FeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Shell Material, Finish	Thermoplastic
Voltage - Rated250VCurrent Rating2A	Contact Finish	Gold
Current Rating 2A	Features	Spring Probe
	Voltage - Rated	250V
Report errors?	Current Rating	2A
		Report errors?

1445322-5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 1445322-5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com