

1445756-1

1445756-1 Information



Part Number	1445756-1	
Manufacturer	TE Connectivity AMP Connectors	
Category	Connectors, Interconnects Circular Connectors	
Description	CONN RCPT CPC 19POS FREE SLDTAIL	
Package	-	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1445756-1 Specifications

Manufacturer Part Number 1445756-1 Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Category Circular Connectors Package - Series Micro CPC Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert Mi3.5 Mounting Type Free Hanging (In-Line) Yernination Solder Orientation Keyed Orientation Keyed Shell Material, Finish Thermoplastic Shell Material, Finish Solder Contact Finish Solder Contact Finish Solder Voltage - Rated Spring Probe		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesMicro CPCConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size, MIL-Mounting TypeSolderTerminationSolderFastening TypeConder Contert Sign MitOrientationP65 - Dust Tight, Water ResistantShell Material, FinishGoldContact FinishGoldFeaturesSpring ProbeVoltage - RatedSpring ProbeCurrent RatingSolowCurrent RatingSolow <td>Manufacturer Part Number</td> <td>1445756-1</td>	Manufacturer Part Number	1445756-1
Circular ConnectorsPackage-SeriesMicro CPCConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - InsertM13.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationH95 - Dust Tight, Water ResistantShell Material, FinishGoldContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Manufacturer	TE Connectivity AMP Connectors
Package-SeriesMicro CPCConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - InsertM13.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedShell Material, FinishP65 - Dust Tight, Water ResistantShell Material, FinishGoldFeaturesSpring ProbeVoltage - RatedSpring ProbeCurrent Rating2A	Category	Connectors, Interconnects
SeriesMicro CPCConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - InsertM13.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationH95 - Dust Tight, Water ResistantShell Material, FinishGoldForturesSolderContact FinishGoldFasteningSpring ProbeContact FinishSpring Probe <td></td> <td>Circular Connectors</td>		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions19Shell Size - InsertM13.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationM55 - Dust Tight, Water ResistantShell Material, FinishGoldContact FinishSpring ProbeFasturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Package	-
Number of Positions19Shell Size - InsertM13.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Series	Micro CPC
Shell Size - InsertM13.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishGoldContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Connector Type	Receptacle, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishGoldContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Number of Positions	19
Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Shell Size - Insert	M13.5
TerminationSolderFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Shell Size, MIL	-
Fastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Mounting Type	Free Hanging (In-Line)
OrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Termination	Solder
Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Fastening Type	Latch Lock
Shell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Orientation	Keyed
Contact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Ingress Protection	IP65 - Dust Tight, Water Resistant
FeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Shell Material, Finish	Thermoplastic
Voltage - Rated250VCurrent Rating2A	Contact Finish	Gold
Current Rating 2A	Features	Spring Probe
	Voltage - Rated	250V
Report errors?	Current Rating	2A
		Report errors?

1445756-1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 1445756-1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com