

14A-10R-28 Information



For Reference Only

Part Number 14A-10R-28

Manufacturer Signal Transformer

Category Transformers

Power Transformers

Description XFRMR LAMINATED 10VA THRU HOLE

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









14A-10R-28 Specifications

Manufacturer Part Number14A-10R-28ManufacturerSignal TransformerCategoryTransformersPackage-SeriesOne-4-All?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 720mA, Series 360mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.70mm WHeight - Seated (Max)34.90mmVoltage - Isolation4000VrmsWeight0.53 lb (240.4g)		
Category Transformers Package - Series One-4-All? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 720mA, Series 360mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) 34.90mm Voltage - Isolation 4000Vrms Weight 0.53 lb (240.4g)	Manufacturer Part Number	14A-10R-28
Power Transformers	Manufacturer	Signal Transformer
Package - Series One-4-All? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 720mA, Series 360mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) 34.90mm Voltage - Isolation 4000Vrms Weight 0.53 lb (240.4g)	Category	Transformers
Series One-4-All? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 720mA, Series 360mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) 34.90mm Voltage - Isolation 4000Vrms Weight		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 720mA, Series 360mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) 34.90mm Voltage - Isolation 4000Vrms Weight 0.53 lb (240.4g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 720mA, Series 360mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) Voltage - Isolation Weight 4000Vrms Weight	Series	One-4-All?
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 720mA, Series 360mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 14V, Series 28V Parallel 720mA, Series 360mA Parallel 720mA, Series 360mA Parallel 720mA, Series 28V Parallel 720mA, Series 360mA Parallel 720mA, Series 28V Dual Secondary Winding(s) A	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 720mA, Series 360mA Dual Pual Pual Pom No Powar No Powar No Powar No	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) Voltage - Isolation 4000Vrms Weight	Voltage - Secondary (Full Load)	Parallel 14V, Series 28V
Secondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.70mm WHeight - Seated (Max)34.90mmVoltage - Isolation4000VrmsWeight0.53 lb (240.4g)	Current - Output (Max)	Parallel 720mA, Series 360mA
Center Tap Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) Voltage - Isolation 4000Vrms Weight No 10 VA Through Hole PC Pin 47.60mm L x 39.70mm W 34.90mm 40.53 lb (240.4g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) Voltage - Isolation 4000Vrms Weight 0.53 lb (240.4g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) 34.90mm Voltage - Isolation 4000Vrms Weight 0.53 lb (240.4g)	Center Tap	No
Termination Style PC Pin Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) 34.90mm Voltage - Isolation 4000Vrms Weight 0.53 lb (240.4g)	Power - Max	10 VA
Size / Dimension 47.60mm L x 39.70mm W Height - Seated (Max) 34.90mm Voltage - Isolation 4000Vrms Weight 0.53 lb (240.4g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 34.90mm 4000Vrms 0.53 lb (240.4g)	Termination Style	PC Pin
Voltage - Isolation 4000Vrms Weight 0.53 lb (240.4g)	Size / Dimension	47.60mm L x 39.70mm W
Weight 0.53 lb (240.4g)	Height - Seated (Max)	34.90mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	0.53 lb (240.4g)
Traport virusion		Report errors?

14A-10R-28 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

14A-10R-28 Payment Methods





















14A-10R-28 Shipping Methods













If you have any question about 14A-10R-28, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com