

14A-20-36B40

14A-20-36B40 Information

Heisener.com	Part Number Manufacturer Category Description Package	14A-20-36B40 Pulse Electronics Power Transformers Power Transformers XFRMR LAMINATED 20VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



14A-20-36B40 Specifications

Manufacturer Part Number14A-20-36B40ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.12A, Series 560mAPrimary Winding(s)Single, Multiple TapsConter TapNoPower - Max20 VAMounting TypePringu HoleSize / DimensionSr.15mm Lx 47.63mm WHeight - Seated (Max)4.128mmVoltage - Isolation-Weight0.916 (408.23g)		
CategoryTransformersCategoryFransformersPockage-Package-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.12A, Series 560mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleSize / DimensionS7.15mm L x 47.63mm WSize / Dimension41.28mmVoltage - Isolation9.09 Ib (408.23g)	Manufacturer Part Number	14A-20-36B40
Power TransformersPackage-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.12A, Series 560mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleSize / Dimension57.15mm L x 47.63mm WSize / Dimension41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Manufacturer	Pulse Electronics Power
Package-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - PrimaryI15V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 360Current - Output (Max)Parallel 1.12A, Series 560mACurrent - Output (Max)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StyleSr.15mm Lx 47.63mm WStez / Dimension41.28mmVoltage - Isolation9.01 (Wats.23g)	Category	Transformers
SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.12A, Series 560mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StyleS7.15mm Lx 47.63mm WSize / Dimension41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.12A, Series 560mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StyleS7.15mm L x 47.63mm WSize / Dimension41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Package	-
TypeInterformVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.12A, Series 560mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Series	International PC Plug-In
Voltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 1.12A, Series 560mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Туре	Laminated Core
Current - Output (Max)Parallel 1.12A, Series 560mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)-Voltage - Isolation-Weight0.9 lb (408.23g)	Voltage - Secondary (Full Load)	Parallel 18V, Series 36V
Secondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)-Voltage - Isolation-Weight0.9 lb (408.23g)	Current - Output (Max)	Parallel 1.12A, Series 560mA
Center TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Primary Winding(s)	Dual
Power - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Secondary Winding(s)	Single, Multiple Taps
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Center Tap	No
Termination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Power - Max	20 VA
Size / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Mounting Type	Through Hole
Height - Seated (Max)41.28mmVoltage - Isolation-Weight0.9 lb (408.23g)	Termination Style	PC Pin
Voltage - Isolation-Weight0.9 lb (408.23g)	Size / Dimension	57.15mm L x 47.63mm W
Weight 0.9 lb (408.23g)	Height - Seated (Max)	41.28mm
· · ·	Voltage - Isolation	-
Report errors?	Weight	0.9 lb (408.23g)
		Report errors?

14A-20-36B40 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 14A-20-36B40, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com