

14A-30-12B11

14A-30-12B11 Information

Heisener.com	Part Number Manufacturer Category Description Package	14A-30-12B11 Pulse Electronics Power Transformers Power Transformers XFRMR LAMINATED 30VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



14A-30-12B11 Specifications

Manufacturer Part Number14A-30-12B11ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)Single, Multiple TapsCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StyleSecondary Minding(s)Size / Dimension66.68mm L x 55.55mm WVoltage - Isolation-WeightLa (La Sug)		
CategoryTransformersPower TransformersPackage-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)Single, Multiple TapsCenter TapNoPower - Max30 VAPower - MaxSingle, Multiple TapsMounting TypeFrough HoleTermination StyleCenter AgeSize / Dimension6.68mm Lx 55.55mm WSize / Dimension9.97mmHeight - Seated (Max)9.07mmVoltage - Isolation1.2 lbs (544.3g)	Manufacturer Part Number	14A-30-12B11
Power TransformersPackage-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StyleSecondary Mathematication StyleSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Manufacturer	Pulse Electronics Power
Package-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - MaxSingle, Multiple TapsNounting TypeDivalSter JinensionProngh HoleSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)9.07mmVoltage - Isolation-WeightLaminet ActionWeight1.2 bs (544.3g)	Category	Transformers
SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max30 VAMounting TypeProluge HoleSize/ Dimension668mm L x 55.55mm WSize/ Dimension39.67mmHeight - Seated (Max)3.07mmWeight1.2 lbs (544.3g)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination Style66.68mm L x 55.55mm WSize / Dimension39.67mmHeight - Seated (Max)-Woingte - Isolation1.2 lbs (544.3g)	Package	-
Name Name Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 30 VA Mounting Type Through Hole Termination Style 66.68mm L x 55.55mm W Size / Dimension 39.67mm Height - Seated (Max) 39.67mm Voltage - Isolation 1.2 lbs (544.3g)	Series	International PC Plug-In
Voltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Туре	Laminated Core
Current - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.8mm L x 55.5mm WHeight - Seated (Max)99.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)99.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Voltage - Secondary (Full Load)	Parallel 6.3V, Series 12.6V
Secondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Current - Output (Max)	Parallel 4.8A, Series 2.4A
Center TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Primary Winding(s)	Dual
Power - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Secondary Winding(s)	Single, Multiple Taps
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Center Tap	No
Termination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Power - Max	30 VA
Size / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Mounting Type	Through Hole
Height - Seated (Max)39.67mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Termination Style	PC Pin
Voltage - Isolation-Weight1.2 lbs (544.3g)	Size / Dimension	66.68mm L x 55.55mm W
Weight 1.2 lbs (544.3g)	Height - Seated (Max)	39.67mm
	Voltage - Isolation	-
Report errors?	Weight	1.2 lbs (544.3g)
		Report errors?

14A-30-12B11 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

14A-30-12B11 Payment Methods



14A-30-12B11 Shipping Methods



If you have any question about 14A-30-12B11, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com